

## Drench Showers



Model 8100 drench shower features a 10" ABS plastic shower head in Safety Green. Floor mounted by a floor flange assembly and hot dip galvanized steel pipe with high visibility stripes in Safety Green and bright yellow. A stainless steel pull rod operates a stay open chrome-plated brass ball valve that is equipped with a stainless steel stem. All Haws emergency equipment models are certified by CSA to meet the ANSI Z358.1-1998 Standard for Emergency Eyewash and Shower Equipment. Supply: 1-1/4" IPS.

### Components:

**Shower Head:** Model 8129, molded ABS plastic 10" shower head with perforated spreader in Safety Green. Corrosion resistant against alkalis, oils and most acids.

**Shower Valve:** Model SP260 chrome-plated brass stay-open ball valve, equipped with a stainless steel stem. Full flow occurs with pull on lever. 1" IPS.

**Mounting:** Model SP75 grey powder-coated cast-iron floor flange with 1-1/4" IPS hot-dip galvanized tee. Diameter 9" with three 3/8" mounting holes.

**Pull Rod:** Model SP200, 28" long stainless steel pull rod with triangular handle.

**Universal Sign:** Model SP177 vertical universal emergency shower sign. Size: 8" x 11".

**High-Visibility Stripe:** Model SP185 self-adhesive high visibility 21" long stripe in Safety Green and bright yellow.

**Test This Week Tag:** Model SP170 green waterproof test card with space for date and initials of inspector. Used to record weekly testing of emergency equipment.

## 8100



### Options & Accessories: (Additional cost)

**Colors & Finishes:** CRP special green powder-coating provides extra protection against corrosive environments.

**Tempered Water Blending Systems:** Model 9202 thermostatic mixing valve that mixes of hot and cold water for the tempering of water for eyewash and showers. Maximum flow rate is 60 gpm.

**Tempered Water Blending Systems:** Model TWBS.SH tempered water blending system with redundant fail-safe features, prepackaged, fully engineered and tested system for mixing large volumes of hot and cold water to provide tempered water for showers and eyewashes.

**Hose & Spray Unit:** Model 8901RFK eye/face wash and body spray with 8-foot pressure rated hose. Includes retrofit kit to accommodate installation on many combination showers and eyewash units.

**Shower Head:** Model 8127, corrosion resistant, high polished stainless steel 10" shower head with perforated stainless steel spreader.

**Privacy Curtain:** Model 9037 privacy curtain designed to be used on horizontal emergency drench shower or combination emergency drench shower and eyewash units.

**Alarm:** Model 9001 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by flow switch when emergency shower or eyewash is in use.

**Universal Sign:** Model 9021 green and yellow ABS plastic 3-sided sign for use with emergency drench showers.