Declaration of Performance according to Annex III of the regulation EU no. 305/2011

Protega Novatherm SP

DoP No: 4151

1: Product type (Identification code of the product)

Protega Novatherm SP

2: Type
(Batch or serial number or as

(Batch or serial number or any other element allowing identification of the product)

See print on the cartridge

3: Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer

Fire Stopping and Sealing Product, Linear Joint and Gap Seal

4: Name, registrated trade name orregistrated trade mark and contact address of the manufacturer as required under Article 11(5)

Protega AB Verkstadsgatan 6B 23166 Trelleborg, Sweden

5: Contact Address

Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)

Not relevant (see 4)

6: AVCP

System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V

System 1

7: Notified body (hEN)

In case of the declaration of performance (DoP) concerning a production product covered by a harmonized standard.

Not relevant

8: Notified body (ETA)

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been isued

European Technical Assessment ETA-19/0042 issued by Warringtonfire Testing and Certification Limited EAD 350141-00-1106 was used as European Assessment Document (EAD).

Protega AB, Verkstadsgatan 6B, 23166 Trelleborg, Sweden Tel: +46 410 56780 E-mail: info@protega.se

9: Declared Performance

Essential characteristics	Performance	Technical specification
Reaction to fire	NPD	EN13501-1
Resistance to fire	See Annex A	EN13501-2
	ETA 19/0042	
Release of dangerous	Use category IA1/ IA2	Declaration by
sustances	Declaration by	manufacturer
	manufacturer	
Airborne sound insulation	D _{new} 57(0;-4)dB & D _{new} 59 (0;-	EN10140-2/ EN ISO 717-1
	4)dB	2
Air permeability	NPD	EN 1026:2000
Water permeability	NPD	EAD 360141-00-1106
Mechanical resistance	NPD	EOTA TR 001:2003
and stability		* 1
Resistance to impact/	NPD	EOTA TR 001:2003
movement		. "
Adhesion	NPD	EOTA TR 001:2003
Thermal properties	NPD	EN 12664, EN 12667 or
	9	EN 12939
Water vapour permeability	NPD	EN ISO 12572 EN 12086
Durability	Z2	EOTA TR 024:2009

10: The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for the manufacturer and on behalf of the manufacturer

Dan Klittbo

Managing Director

Björn Wettermark Technical Support

Trelleborg 2020-01-20

Protega AB, Verkstadsgatan 6B, 23166 Trelleborg, Sweden Tel: +46 410 56780 E-mail: info@protega.se