








LK Clip Rail Combi 16/20

LK Systems AB

Programme: The International EPD® System, www.environdec.com

Programme operator: EPD International AB

EPD registration number: S-P-08142 Publication date: 2023-04-14 Valid until: 2028-04-14



An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com





Company information

	LK Systems AB
Owner of the EPD:	Johannesfredsvägen 7
Owner of the EPD.	168 69 Bromma
	Sweden
Contact	info@lksystems.se
Contact:	https://www.lksystems.se/
Name and location of production	Liljas Plast
site:	Hillerstorp

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterization factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.

Programme information

Programme:	The International EPD® System									
	EPD International AB									
Address:	Box 210 60									
Address.	SE-100 31 Stockholm									
	Sweden									
Website:	www.environdec.com									
E-mail:	info@environdec.com									
CEN standard EN 1	5804 serves as the Core Product Category Rules (PCR)									
Product category ru (1.2.5)	lles (PCR): 2019:14, Construction products (EN 15804:A2)									
PCR review was cor the International EP	nducted by: Claudia A. Peña, The Technical Committee of D® System.									
Contact: info@envir	ondec.com									
Independent third-p ISO 14025:2006:	arty verification of the declaration and data, according to									
☐ EPD process cert	ification ⊠ EPD verification									
Third party verifier:	Daniel Böckin, PhD									
Miljögiraff AB, danie	el@miljogiraff.se									
Approved by: The In	ternational EPD® System.									





Company information

LK Systems is the leading manufacturer of easy-to-install systems for heating and tap water distribution in the Nordic region. Our prefabrication factory provides customized solutions to simplify the installation process even further. From idea to final solution, you can be sure of the smartest answers for your everyday challenges, today and tomorrow.

For the simpler, smarter everyday

Simpler. Smarter. More sustainable. At LK, we believe there's a better way to do everything. That's why – from water, heating and hydronic solutions to pipe extrusion – we push for innovation over status quo and simplicity over complexity. It's a belief all of us at LK apply to every product and solution we create.

Product	Product number
Clip Rail Combi 16/20, nails	2410457
Clip Rail Combi 16/20 no nails	2410456

Product information

The Clip Rail is a 10,2-meter-long product that comes folded up and is quick and easy to install. The consumption rate for the Clip Rail is 0,12 units per square meter.

There are two versions of the Clip Rail available, both of which are manufactured from recycled plastic. The first version features inbuilt barbed staples (nails) and is suitable for use when laying EPS insulation. The second version does not have barbed staples and is secured in place on the slab using concrete nails and a nail gun.

Further information can be found at https://www.lksystems.se/

The EPD represents several product versions and is a representative value based on Clip Rail Combi 16/20, nails as the declared unit. The results presented in the EPD show the results of the representative product, with variations staying within 10% (GWP-GHG). Please see the appendix for the total weight of the products included in the EPD.





LCA information

Functional unit / declared unit	In accordance with EN 15804 + A2 the declared unit is 1 kg of mass.
Time representativeness:	2022
Database:	Ecoinvent 3.8 "allocation cut off by classification" is used throughout the study.
LCA software used:	SimaPro 9.4.0.2
Geographical scope	Production: Sweden Construction site: Sweden
LCA Report	LK Systems AB, Report no. 11

Description of system boundaries:

The scope of the EPD is cradle to gate with options, including A4, A5, C, and D. Table 1 shows the declared modules. The system boundary includes all processes needed for raw material extraction, transport, manufacturing, and disposal. Figure 1 provides an overview of the included processes.

	Prod	luct sta	age	cti	stru- on cess ige	Use stage					En	End of life stage				Resource recovery stage		
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal		Reuse-Recovery-Recycling- potential
Module	A1	A2	А3	Α4	A5	В1	B2	ВЗ	B4	В5	В6	В7	C1	C2	C3	C4		D
Modules declared	Х	Х	Χ	Χ	Χ	ND	ND	ND	ND	ND	ND	ND	Χ	Χ	Χ	Χ		X
Geography	SE	SE	SE	SE	SE								SE	SE	SE	SE		SE
Specific data used		>(90%			-	-	-	-	-	-	-	-	-	-	-		-
Variation, products		<	10%			-	-	-	-	-	-	-	-	-	-	-		-
Variation, sites		-	0%			-	-	-	-	-	-	-	-	-	-	-		-
X = Modules included in the analysis ND = Module not declared 0= Optional modules																		

Table 1, Modules declared, geographical scope, share of specific data (in GWP-GHG indicator) and data variation.





Recycling D

Material

recycling

Heat from

energy recovery

Content information

Table 2, shows the weight of the raw material of the declared product.

Product components	Weight, kg	Pre-consumer material, weight-%	Post-consumer material, weight-%	Renewable material, weight-%							
Recycled plastic	1	100	0	0							
TOTAL	1	100	0	0							
Packaging materials	Weight, kg	Weight-% (versus the	/eight-% (versus the product)								
Cardboard box	0,007	0,7									
Plastic	0,01	1									
Pallet	0,00007	0,007									
TOTAL	0,02	2									

The declared product contains no dangerous substances from the candidate list of SVHC for Authorization.




Figure 1, overview of the included processes. Light gray represents modules included. Yellow represents modules not declared.











Product life-cycle

Raw material supply, transport, manufacturing and packaging (A1-A3)

The recycled plastic, which accounts for 100% of the product, is produced in Sweden, and specific modulated data from the supplier is used.

The manufacturing process takes place in Sweden and includes the manufacturing of the raw materials used for the final product, as well as the process of assembling the product. After the manufacturing of the product is completed, it is packed in a cardboard box wrapped in plastic bands, which is then stacked on a pallet.

See figure 2 below for the process flow step by step.



Figure 2, Production process flow.





Transport & installation (A4-A5)

Transportation impacts represent the transport from the final product's delivery to the construction site. The transport distance is based on the average distance and is performed by truck using fuel. It is assumed that there are no environmental aspects during the installation of the product, except for the waste management of the packaging after installation.

Product End-of-Life (C1-C4, D)

The end-of-life stage (C1) of the product is assumed to have no environmental impacts during the demolition of the product. When the building where the product is installed is demolished, it is assumed that the product will be material recycled at 13% (Naturvårdsverket, 2023), while the remaining 87% will end up in combustible waste.

The cardboard box is assumed to be material recycled at 78% (Fråne, A. et al., 2021), while the remaining 22% is assumed to end up in combustible waste. The product and packaging are assumed to be sent to the nearest waste facility. In the resource recovery stage, the benefits will be mostly energy recovery, with a smaller portion dedicated to material recycling for the packaging since the material for the product is already made from recycled materials.

Cut-off rules

According to EN 15804, life cycle inventory data shall include a minimum of 95% of total inflows (mass and energy) per module. If less than 100% of the inflows are accounted for, proxy data or extrapolation should be used to achieve 100% completeness.

Background data

The data quality of the background data is considered good. All specific data, including processes, volume of different materials, energy usage, and transport distance, has been collected by questionnaire and through personal contact with the manufacturer. The Ecoinvent database, which is the world's largest LCI data library, has been used. It contains data for specific geographical regions relevant to this study, which have been analyzed to be the most suitable for the various steps in the process. Information on biogenic carbon content is calculated using the formula from EN 350-2 and information from IVL. The collected data represent average yearly data for 2022 and are assumed to be representative for the EPDs period of validity of 5 years.

Electricity data

The electricity used is a modulated fossil-free mix from "Eon" in Sweden (2022), where 5% is renewable primary energy, and 95% is nuclear. The electricity used in stage A3 accounts for less than 30% of the total energy used in stages A1-A3.





Allocation and assumptions

The declared unit values for 1 kg of the product used in this study are calculated based on the total weight of the product produced during the year under study. The content of raw materials can vary slightly between different product dimensions and is examined with high accuracy to ensure that the variation of GWP-GHG stays within 10%. Data is allocated for the energy use of the declared unit based on production rate with complexity and high accuracy. The raw materials necessary for manufacturing and the amount of packaging allocated to the product are based on the amount of material used to manufacture the declared unit, including waste. The allocation is made with complexity and high accuracy. The declared unit is based on Clip Rail Combi 16/20, nails and the variance of the declared products is less than 10%, based on the data quality requirements outlined in PCR 2019:14.

The used product is assumed to be transported 50 km to the nearest waste disposal facility. The waste treatment assumption has resulted in the product being material recycled as plastic. The waste treatment assumes that the product is installed in the building and deconstructed when the building is demolished. The product is assumed to be material recycled at 13%, and the cardboard box is assumed to be material recycled at 78%. The remaining plastic in the product and the plastic packaging are assumed to be incinerated with energy recovery efficiency at 61%.



Recycling of packaging and product

As part of our producer responsibility framework, LK is affiliated with FTI, the Packaging and Newspaper Collection, which is the business community's collection system for recycling packaging. The product is to be recycled as plastic and the packaging as cardboard and plastic. None of the recycled materials are classified as hazardous waste.





Environmental information

Potential environmental impact – mandatory indicators according to EN 15804. Results of declared unit of the study.

Indicator	Unit	Tot.A1-A3	A4	A5	C1	C2	C3	C4	D
GWP-fossil	kg CO2 eq.	6,02E-01	7,68E-02	2,36E-02	0	6,56E-03	2,04E+00	0	-6,03E-02
GWP-biogenic	kg CO2 eq.	-1,29E-02	6,91E-05	2,44E-03	0	6,41E-06	2,73E-04	0	-5,09E-03
GWP-luluc	kg CO2 eq.	5,04E-03	3,02E-05	5,18E-07	0	2,67E-06	4,00E-05	0	-6,14E-04
GWP-total	kg CO2 eq.	5,94E-01	7,69E-02	2,61E-02	0	6,57E-03	2,04E+00	0	-6,60E-02
ODP	kg CFC 11 eq.	5,87E-08	1,78E-08	1,91E-10	0	1,54E-09	1,37E-08	0	-1,69E-08
AP	mol H+ eq.	1,42E-03	3,12E-04	7,20E-06	0	3,72E-05	5,20E-04	0	-2,21E-03
EP-freshwater	kg P043- eq	1,62E-04	1,52E-05	4,52E-07	0	1,36E-06	3,59E-05	0	-5,47E-05
EP-freshwater	kg P eq.	5,27E-05	4,95E-06	1,47E-07	0	4,43E-07	1,17E-05	0	-1,78E-05
EP-marine	kg N eq.	5,09E-04	9,39E-05	3,57E-06	0	1,35E-05	2,65E-04	0	-6,46E-04
EP-terrestrial	mol N eq.	3,93E-03	1,03E-03	3,24E-05	0	1,47E-04	2,36E-03	0	-1,06E-02
POCP	kg NMVOC eq.	1,26E-03	3,14E-04	8,34E-06	0	4,21E-05	6,02E-04	0	-1,81E-03
ADP-minerals&metals ²	kg Sb eq.	2,01E-06	2,67E-07	4,29E-09	0	2,20E-08	3,30E-07	0	-2,21E-07
ADP-fossil ²	MJ	4,85E+01	1,16E+00	6,77E-03	0	1,01E-01	3,93E-01	0	-7,31E-01
WDP ²	m3	5,73E-01	3,48E-03	2,92E-04	0	3,32E-04	2,40E-02	0	-9,60E-03

Acronyms

GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic;

GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer;

AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients Innreaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment;

EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone;

ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential;

WDP = Water (user) deprivation potential, deprivation-weighted water consumption





Potential environmental impact - additional mandatory indicators according to EN 15804.

Indicator	Unit	Tot.A1-A3	A4	A5	C1	C2	C3	C4	D
Particulate matter	disease inc.	3,16E-08	6,63E-09	1,02E-10	0	7,26E-10	3,55E-09	0	-3,04E-08
Ionnising radiation ¹	kBq U-235 eq	3,14E+00	5,97E-03	4,84E-05	0	5,21E-04	3,23E-03	0	-6,62E-03
Ecotoxicity, freshwater ²	CTUe	1,04E+01	9,06E-01	6,79E-02	0	8,00E-02	5,50E+00	0	-2,19E+01
Human toxicity, cancer ²	CTUh	3,31E-10	2,94E-11	4,84E-12	0	3,19E-12	4,07E-10	0	-2,57E-10
Human toxicity, non-cancer ²	CTUh	3,77E-09	9,53E-10	4,99E-11	0	9,23E-11	3,81E-09	0	-8,87E-09
Land use ²	Pt	8,70E+00	7,98E-01	2,93E-03	0	8,62E-02	1,17E-01	0	-4,55E+01

Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 - The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.

Climate impact IPCC GWP 100

Indicator	Unit	Tot.A1-A3	A4	A 5	C1	C2	C3	C4	D
GWP-GHG	kg CO2 eq.	6,06E-01	7,62E-02	2,36E-02	0	6,51E-03	2,04E+00	0	-5,98E-02

The indicator includes all greenhouse gases included in GWP-total but excludes biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. This indicator is thus almost equal to the GWP indicator originally defined in EN 15804:2012+A1:2013.





Use of resources

Indicator	Unit	Tot.A1-A3	A4	A5	C1	C2	C3	C4	D
PERE	MJ	4,38E+00	1,64E-02	4,61E-04	0	1,45E-03	3,64E-02	0	-1,08E+01
PERM	MJ	5,27E-01	0	0	0	0	0,00E+00	0	0,00E+00
PERT	MJ	4,90E+00	1,64E-02	4,61E-04	0	1,45E-03	3,64E-02	0	-1,08E+01
PENRE	MJ	5,24E+01	1,23E+00	7,23E-03	0	1,07E-01	4,21E-01	0	-7,77E-01
PENRM	MJ	0,00E+00	0	0	0	0	0,00E+00	0	0,00E+00
PENRT	MJ	5,24E+01	1,23E+00	7,23E-03	0	1,07E-01	4,21E-01	0	-7,77E-01
SM	kg	1,00E+00	0	0	0	0	0,00E+00	0	0,00E+00
RSF	MJ	0,00E+00	0	0	0	0	0,00E+00	0	0,00E+00
NRSF	MJ	0,00E+00	0	0	0	0	0,00E+00	0	0,00E+00
FW	m3	1,61E-02	1,94E-04	1,57E-05	0	1,87E-05	1,11E-03	0	-4,70E-04

Acronyms

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials;

PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources;

PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials;

PENRM = Use of non-re- newable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources;

SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels;

FW = Use of net fresh water





Waste production and output flows

Waste production

Indicator	Unit	Tot.A1-A3	A4	A5	C1	C2	C3	C4	D
Hazardous waste disposed	kg	0	0	0	0	0	0	0	0
Non-hazardous waste disposed	kg	0	0	0	0	0	0	0	0
Radioactive waste disposed	kg	0	0	0	0	0	0	0	0

Note: Ecoinvent database include all waste treatment processes within the system boundaries, i.e. there are no waste flows exiting the system boundaries and the waste indicators to be declared are therefore zero.

Output flows

Indicator	Unit	Tot.A1-A3	A4	A5	C1	C2	C3	C4	D
Components for re-use	kg	0	0	0	0	0	0	0	0
Material for recycling	kg	0	0	1,55E-02	0	0	1,30E-01	0	0
Materials for energy recovery	kg	0	0	0	0	0	0	0	0
Exported energy, electricity	MJ	0	0	0	0	0	0	0	0
Exported energy, thermal	MJ	0	0	0	0	0	0	0	0





Information on biogenic carbon content

Results per functional or declared unit

Biogenic carbon content	Unit	Quantity
Biogenic carbon content in product	kg C	0
Biogenic carbon content in packaging	kg C	2,21E-03

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2.

Additional information

Product	Product number	Weight (kg)	Weight with packaging (kg)
Clip Rail Combi 16/20, nails	2410457	2,10	2,14
Clip Rail Combi 16/20 no nails	2410456	1,97	2,01





References

General Programme Instructions of the International EPD® System. Version 4.0.

PCR Construction Products. 2019:14, version 1.2.5, the International EPD System, Date 2022-11-01.

EN 15804:2012+A2:2019/AC:2021, "Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products"

EN ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures, Edited in 2010

EN ISO 14040:2006 Environmental management - Life cycle assessment - Principles and framework, 2006.

EN ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines, 2006.

PRé Consultants, "SimaPro 9.4.0.2" (PRé Consultants, 2019), http://www.pre-sustainability.com/simapro

Ecoinvent, 'Ecoinvent', https://www.ecoinvent.org/database/database.html

Eriksson, E. et al., (2010) Carbon Footprint of Cartons in Europe – Carbon Footprint methodology and biogenic carbon sequestration, IVL. Carbon footprint of cartons in Europe – Carbon Footprint methodology and biogenic carbon sequestration (ivl.se)

EUTREND model, Struijs et al, 2009b, as implemented in ReCiPe; http://eplca.jrc.ec.europa.eu/LCDN/developerEF.xhtml

Energy mix, Sweden: (Fördelningen av elproduktion för de olika kraftslag 2021) https://www.energimyndigheten.se/nyhetsarkiv/2022/fortsatt-hog-elproduktion-och-elexport-under-2021/ (2023-03-06)

Material recycling paper: Fråne, A. et al., (2021) Sveriges återvinning av förpackningar och tidningar, Naturvårdsverket. https://www.naturvardsverket.se/contentassets/568ba7678ce94e25b99cfc1b02ad7e2a/forpackningsrapport_2020_211027.pdf

Material recycling plastic: Naturvårdsverket 2023-03-06 https://www.naturvardsverket.se/amnesomraden/plast/

Energy losses in Sweden: SCB 2023-04-05

https://www.statistikdatabasen.scb.se/pxweb/sv/ssd/START_EN_EN0108_EN0108A/ElanvM/