Environmental

Product Declaration

In accordance with ISO 14025 and EN 15804:2012+A2:2019 for:

Altech Panel Radiators

from

Saint-Gobain Building Distribution (SGDS)



Programme:	The International EPD [®] System, www.environdec.com
Programme operator:	EPD International AB
EPD registration number:	S-P-06735
Publication date:	2022-09-01
Valid until:	2027-08-31

An EPD should provide current information and may be updated if conditions change. The stated validity is therefore subject to the continued registration and publication at www.environdec.com









General information

Programme information

Programme:	The International EPD [®] System						
	EPD International AB						
Address:	Box 210 60						
Address.	SE-100 31 Stockholm						
	Sweden						
Website:	www.environdec.com						
E-mail:	info@environdec.com						

Accountabilities for PCR, LCA and independent, third-party verification

Product Category Rules (PCR)

CEN standard EN 15804 serves as the Core Product Category Rules (PCR)

Product Category Rules (PCR): PCR 2019:14 Construction products. Version 1.11, date 2021-02-05.

PCR review was conducted by: The Technical Committee of the International EPD® System. Chair: Claudia A. Peña. Contact via info@environdec.com

Life Cycle Assessment (LCA)

LCA accountability: Simon Andersson, IVL Swedish Environmental Research Institute

Third-party verification

Independent third-party verification of the declaration and data, according to ISO 14025:2006, via:

 \boxtimes EPD verification by individual verifier

Third-party verifier: Vladimír Kočí, Prague, Czech Republic, Icastudio.cz

Approved by: The International EPD® System

Procedure for follow-up of data during EPD validity involves third party verifier:

 \Box Yes \boxtimes No

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but from different programmes may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804. For further information about comparability, see EN 15804 and ISO 14025.



Company information

<u>Owner of the EPD:</u> Saint-Gobain Distribution Sweden

<u>Contact:</u> SGDS - Beriar Maroof (beriar.maroof@sgdsgruppen.se) Optimera - Henrik Björk (henrik.bjork@optimera.se)

Description of the organisation:.

SGDS Gruppen AB is the mother company of some of Sweden's leading trading companies of distribution of building material within construction products, sheet metal, tiles and installation products for plumbing, heating and sanitary.

• Optimera - construction products

- Dahl plumbing, heating, sanitary, civil engineering, industry, cooling and facility management
- Bevego sheet metal, ventilation and technical insulation
- Kakelspecialisten and Konradssons Tiles tiles, tiling and bathroom equipment

The company's focus on sales and services to professional customers with direct contact to about 150 000 customers on a regular basis.

Saint-Gobain Distribution Sweden group (SGDS Gruppen AB) is owned by Saint-Gobain with presence in 64 countries and having over 190 000 employees worldwide.

Product-related or management system-related certifications: ISO9001 and ISO14001

Location of production site: Turkey

Product information

Product name: Altech panel radiator

<u>Product identification:</u> Models K11, K21, K22 and K33. All variants (all lengths and heights)

Product description:

Steel panel radiator produced in steel FePo1 AM in color RAL9016. Steel thickness accordingly to EN442, 1.20 +/- 0.09 mm. To be used for heating in commercial and private property and housing. Expected service lifetime is 50 years.

UN CPC code: 44823

UNSPSC code: 40101801

Geographical scope: The Nordic countries





LCA information

Declared unit: 1 kg Altech panel radiator product

Time representativeness:

The data used to model product manufacturing corresponds to year 2021. The data from generic databases are from 2014 - 2021. No data used is older than 10 years.


Database(s) and LCA software used:

Databases used are the Sphera GaBi databases (content version 2022.1). The LCA software used is GaBi (version 10.6).

Description of system boundaries:

Cradle to gate with options, modules C1-C4, module D and with optional module A4.

System diagram:



Steel sheet and paint (powder coating) are transported to a manufacturing plant where the radiators are manufactured. The radiators are transported to a central warehouse from where they are distributed to the final costumers. After use the product is transported to waste processing, and the steel is recycled.



Modules declared, geographical scope, share of specific data (in GWP-GHG indicator) and data variation:

SGDS GRUPPEN

	Pro	oduct sta	age	proc	ruction cess age					Resource recovery stage							
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling- potential
Module	A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Modules declared	х	х	х	х	ND	ND	ND	ND	ND	ND	ND	ND	х	х	х	х	х
Geography	TR	TR	TR	TR- NC	-	-	-	-	-	-	-	-	NC	NC	NC	NC	NC
Specific data used	9%		-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Variation – products	<2%		-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Variation – sites	Ν	ot releva	nt	-	-	-	-	-	-	-	-	-	-	-	-	-	-

X: Module declared, ND: Module not declared, TR: Turkey, NC: The Nordic countries

The results presented reflects the K11 model, which is the worst case as defined in the PCR.

Allocation:

Weight allocation has been applied to allocate the manufacturing data, delivered for the complete plant, to 1 kg Altech panel radiator product.

Data quality:

Site-specific manufacturing data has been retrieved from the manufacturer. The upstream and downstream processes have been modelled based on generic data from databases, for paint production an existing EPD from the paint supplier has been used. The collected data was reviewed according to EN 15804 and is deemed as of good quality.

Cut-off criteria:

The maximum cut-off criteria established by the PCR is 1% of all material and energy flows to a single unit process and 5% of total inflows (mass and energy) per module, e.g. per module A1-A3, A4-A5, C1-C4 and module D. No cut-offs exceeding this limit have been made.



Content information

Product components	Weight, kg	Post-consumer material, weight-%	Renewable material, weight-%
Steel	0.98	Unknown	0%
Paint	0.016	0%	0%
TOTAL	1.0	Unknown	0%
Packaging materials	Weight, kg	Weight-% (versus the proc	duct)
Corrugated fiberboard	0.022	2.2%	
Polyethylene film	0.017	1.7%	
TOTAL	0.039	3.9%	

No substances that appear in the REACH candidate list of SVHC (Candidate List of Substances of Very High Concern) are present or used in the product.

Environmental Information

Potential environmental impact – mandatory indicators according to EN 15804

	Results per 1 kg Altech panel radiator product												
Indicator	Unit	A1	A2	A3	Tot. A1-A3	A4	C1	C2	C3	C4	D		
GWP- fossil	kg CO ₂ eq.	2.9E+00	1.3E-02	5.8E-02	2.9E+00	4.6E-02	3.3E-04	7.2E-03	1.5E-02	2.2E-03	-1.4E+00		
GWP- biogenic	kg CO ₂ eq.	-1.8E-03	1.3E-04	-3.7E-02	-3.9E-02	5.5E-05	-4.6E-07	7.2E-05	3.1E-06	-6.5E-05	-7.7E-04		
GWP- luluc	kg CO ₂ eq.	4.3E-03	1.3E-04	1.0E-04	4.5E-03	5.1E-07	1.9E-06	7.7E-05	1.1E-05	4.1E-06	-3.0E-05		
GWP- total	kg CO ₂ eq.	2.9E+00	1.3E-02	3.0E-02	2.9E+00	4.6E-02	3.4E-04	7.3E-03	1.5E-02	2.1E-03	-1.4E+00		
ODP	kg CFC 11 eq.	7.2E-09	2.1E-18	8.4E-10	8.0E-09	2.6E-15	2.0E-17	1.2E-18	6.5E-15	5.2E-15	-3.2E-15		
AP	mol H⁺ eq.	8.6E-03	1.4E-05	1.6E-04	8.8E-03	1.8E-03	1.9E-06	7.7E-06	1.5E-05	1.6E-05	-2.4E-03		
EP- freshwater	kg PO4 ³⁻ eq.	5.3E-05	2.8E-07	5.3E-06	5.8E-05	3.1E-08	3.1E-09	1.6E-07	3.0E-08	1.1E-08	-9.1E-07		
EP- freshwater	kg P eq.	1.7E-05	9.2E-08	1.7E-06	1.9E-05	1.0E-08	1.0E-09	5.3E-08	9.9E-09	3.7E-09	-3.0E-07		
EP- marine	kg N eq.	1.6E-03	3.8E-06	5.1E-05	1.7E-03	4.5E-04	9.5E-07	2.1E-06	6.3E-06	4.0E-06	-4.7E-04		
EP- terrestrial	mol N eq.	1.7E-02	5.2E-05	5.3E-04	1.8E-02	4.9E-03	1.1E-05	2.9E-05	7.4E-05	4.4E-05	-4.7E-03		
POCP	kg NMVOC eq.	6.1E-03	1.0E-05	2.2E-04	6.3E-03	1.3E-03	1.8E-06	5.6E-06	1.7E-05	1.2E-05	-2.1E-03		
ADP- minerals& metals*	kg Sb eq.	2.0E-06	1.2E-09	8.0E-09	2.0E-06	1.7E-09	2.8E-11	6.9E-10	2.6E-09	2.3E-10	-3.4E-06		
ADP- fossil*	MJ	2.9E+01	1.6E-01	1.6E+00	3.1E+01	5.6E-01	4.5E-03	9.2E-02	5.2E-02	2.9E-02	-1.3E+01		
WDP	m ³	7.8E-01	1.8E-04	1.8E-02	8.0E-01	8.2E-05	3.0E-06	1.0E-04	3.0E-03	2.4E-04	-3.7E+00		
Acronyms	Potential la Accumulat = Eutrophi	and use and l ed Exceedan cation potent	land use chai nce; EP-fresh ial, fraction o	ntial fossil fue nge; ODP = E water = Eutro f nutrients rea tential of trop	Depletion pote ophication pote aching marine	ential of the s ential, fractio e end compar	tratospheric c n of nutrients tment; EP-te	zone layer; A reaching frea rrestrial = Eut	AP = Acidificat shwater end of rophication p	tion potential compartment otential, Accu	, ; EP-marine umulated		

Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marin = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

* Disclaimer: The results of this environmental impact indicator shall be used with care as the uncertainties of these results are high or as there is limited experience with the indicator.



Potential environmental impact – additional mandatory and voluntary indicators

	Results per 1 kg Altech panel radiator product												
Indicator	Unit	A1	A2	A3	Tot. A1-A3	A4	C1	C2	C3	C4	D		
GWP- GHG ¹	kg CO ₂ eq.	2.8E+00	1.2E-02	5.7E-02	2.9E+00	4.5E-02	3.3E-04	7.1E-03	1.5E-02	2.2E-03	-1.3E+00		

Use of resources

	Results per 1 kg Altech panel radiator product													
Indicator	Unit	A1	A2	A3	Tot. A1-A3	A4	C1	C2	C3	C4	D			
PERE	MJ	1.3E+00	1.7E-02	5.3E-01	1.9E+00	2.2E-03	2.6E-04	9.7E-03	6.2E-03	4.3E-03	8.4E-01			
PERM	MJ	0	0	0	0	0	0	0	0	0	0			
PERT	MJ	1.3E+00	1.7E-02	5.3E-01	1.9E+00	2.2E-03	2.6E-04	9.7E-03	6.2E-03	4.3E-03	8.4E-01			
PENRE	MJ	2.9E+01	1.6E-01	1.6E+00	3.1E+01	5.6E-01	4.5E-03	9.2E-02	5.2E-02	2.9E-02	-1.3E+01			
PENRM	MJ.	0	0	0	0	0	0	0	0	0	0			
PENRT	MJ	2.9E+01	1.6E-01	1.6E+00	3.1E+01	5.6E-01	4.5E-03	9.2E-02	5.2E-02	2.9E-02	-1.3E+01			
SM	kg	0	0	0	0	0	0	0	0	0	0			
RSF	MJ	0	0	0	0	0	0	0	0	0	0			
NRSF	MJ	0	0	0	0	0	0	0	0	0	0			
FW	m³	1.9E-02	2.2E-05	5.6E-04	1.9E-02	3.3E-06	2.9E-07	1.2E-05	7.1E-05	7.3E-06	-8.6E-02			
	PERE = U	lse of renewa	ble primary e	nerav exclud	ing renewable	e primary ene	erav resource	s used as ray	v materials. F	PERM = Use	of			

Acronyms PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

¹ The indicator includes all greenhouse gases included in GWP-total but excludes biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. This indicator is thus almost equal to the GWP indicator originally defined in EN 15804:2012+A1:2013.





Waste production and output flows

Waste production

	Results per 1 kg Altech panel radiator product													
Indicator	Unit	A1	A2	A3	Tot. A1-A3	A4	C1	C2	C3	C4	D			
Hazardous waste disposed	kg	1.1E-04	8.4E-12	6.6E-09	1.1E-04	2.3E-12	2.2E-14	4.8E-12	1.0E-12	1.5E-12	2.9E-09			
Non- hazardous waste disposed	kg	8.8E-02	3.7E-05	1.4E-03	8.9E-02	5.2E-05	6.4E-07	2.1E-05	1.6E-03	1.5E-01	1.7E-01			
Radioactive waste disposed	kg	4.2E-06	2.4E-07	8.3E-06	1.3E-05	6.3E-07	5.5E-09	1.4E-07	1.3E-06	3.2E-07	1.4E-06			

Output flows

	Results per 1 kg Altech panel radiator product													
Indicator	Unit	A1	A2	A3	Tot. A1-A3	A4	C1	C2	C3	C4	D			
Components for re-use	kg	0	0	0	0	0	0	0	0	0	0			
Material for recycling	kg	0	0	3.51E-02	3.51E-02	0	0	0	8.00E-01	0	0			
Materials for energy recovery	kg	0	0	0	0	0	0	0	0	0	0			
Exported energy, electricity	MJ	0	0	0	0	0	0	0	0	0	0			
Exported energy, thermal	MJ	0	0	0	0	0	0	0	0	0	0			





References

ISO (2000): ISO 14020:2000, Environmental labels and declarations - General principles

ISO (2006a): ISO 14025:2006, Environmental labels and declarations – Type III environmental declarations – Principles and procedures

General Programme Instructions of the International EPD® System. Version 3.01.

PCR 2019:14 Construction products. Version 1.11.

CEN (2019): EN 15804:2012+A2:2019, Sustainability of construction works – Environmental product declarations – Core rules for the product category of construction products.

