

[print](#) | [close](#)

detailed view of article 3109784
for your search 3109784

name:

customer version	DMSE
production site	Ansbach
measuring principle	ultrasonic
nominal flow	15 m ³ /h
nominal diameter	50 mm
body length	270 mm
connection	FL 50 mm
connection standard	DIN 2501
temperature	150 °C
nominal pressure	25 bar
approval	MID
metrological class volume	class 2 1:100
metrological class energy	dT 3-175K
1st verification	conformity declared
installation position	any position
energy unit	MWh, 3 digits after comma
volume unit	m ³ , 3 digits after comma
strainer	with

interface module 1	without
interface module 2	without
interface module 3	radio 868 OMS
application	heat meter
installation of flow sensor	return
radio key	OMS3_Schlüssel_individuell
temperature sensor	Pt500 5.2 mm Si 3 m MID
temp. sensor installation return sensor	without mounting set
temp. sensor installation forward sensor	without mounting set
drill for temperature sensor	without
power supply	battery D-cell 3.6 VDC
material	brass
product name	SHARKY
property number	
software	F03-003
Tauchhülsen	without
Versandart	standard

value impulse input 1	10 L
value impulse input 2	10 L
value impulse output 1	energy 1 kWh/Imp.
value impulse output 2	volume 1 L/Imp.
cable length (flow sensor - calculator)	3 m
log memory interval 0	month
log memory interval 1	1 day
log memory interval 2	without
M-Bus primary address type	Fix
M-Bus primary address 2 type	Fix
accounting date 1	end of June
accounting date 2	end of december
integration time max. values	15 min
medium	water

radio telegram	775-55
leak detection	deactivated
tariff 1	forward energy
tariff 2	tariff 2 off
tariff 3	tariff 3 off
tariff 4	tariff 4 off
radio	On
packaging	single packaging
outer packaging	without

pps_grundtyp	GA773039
--------------	----------

release status

active

[print](#) | [close](#)