

PV-10 Fire hydrant cabinet, surface-mounted



Description

Basic model fire hydrant cabinets are manufactured from 1,25 mm steel and the reels are made from 1 mm galvanized steel. The cabinet has a welded back wall that strengthens the structure and a reinforced door. The doors open 180 degrees.

A surface-mounted cabinet can be partially sunk into the wall to the desired depth by using a separate flush-mounting frame.

Standard

Manufactured according to EN 671-1 standard specifications.

Surface finish

Epoxy powder-coated

Standard colours:

- grey (RAL 7040)
- white (RAL 9016)
- red (RAL 3020)

Hoses

1. Fabric surface polyester/EPDM lightweight hose. Fulfills EN 694:2001 standard.

Operating pressure: 1,2 MPa

Burst pressure: 9 MPa

2. Nitrile/PVC fire hydrant hose reinforced with polyester webbing. Fulfils EN 694:2001 Type A Class 2 standard.

Operating pressure: 1,2 MPa

Burst pressure: 4 MPa

The hose assembly is equipped with a spray nozzle.

Reel

The reels are painted red. The hub of the reel is made from a special pressure-tested brass casting. The reel is equipped with a spring-reinforced feed hose, a spray nozzle and a 1" shut off valve.

Lock

The door is equipped with a special lock that is shielded by a breakable protective glass (picture on the right).



Hose size alternatives

Code	Model	Size	Colour
2953302	PV-10	*19 mm/20 m	grey
2953304	PV-10	*19 mm/25 m	grey
2953306	PV-10	*19 mm/30 m	grey
2953308	PV-10	19 mm/40 m	grey
2953310	PV-10	19 mm/45 m	grey
2953312	PV-10	*25 mm/20 m	grey
2953314	PV-10	25 mm/25 m	grey
2953316	PV-10	25 mm/30 m	grey
2953392	PV-10	*19 mm/20 m	white
2953393	PV-10	*19 mm/25 m	white
2953394	PV-10	*19 mm/30 m	white
2953396	PV-10	19 mm/40 m	white
2953397	PV-10	19 mm/45 m	white
2953402	PV-10	*25 mm/20 m	white
2953403	PV-10	25 mm/25 m	white
2953404	PV-10	25 mm/30 m	white
*= also available 245 depth.			

Dimensions

