

The logo for Aistin Level features a stylized icon of two overlapping arrows, one pointing left (orange) and one pointing right (teal), followed by the word "Aistin" in a teal sans-serif font and "Level" in an orange sans-serif font below it.


Aistin Level

Aistin Level —
on another level

Measure any surface level and its properties

The IoTrack logo consists of a stylized icon of two overlapping arrows, one pointing left (orange) and one pointing right (teal), followed by the word "IoTrack" in a teal sans-serif font.

IoTrack

The iprotoxi logo features a stylized 'X' icon composed of two overlapping lines, one orange and one white, followed by the word "iprotoxi" in a white sans-serif font and "energy-efficient industrial IoT" in a smaller white sans-serif font below it.

iprotoxi
energy-efficient industrial IoT

Teknologiantie 18
90590 Oulu, Finland

info@iprotoxi.fi

Aistin Level accurately measures any surface level and its properties, while blending smoothly to the environment around it. The design is modern, elegant, functional - **energy-efficient, completely wireless and ready with software.** We believe devices should be pleasant and easy to use.

The Device

On another level

Elegant & Functional: Our Aistin Design casing seals in all the sensors – object distance, ambient temperature, and orientation, making the device robust and waterproof.

Energy-efficient: Smart power control enables longer than usual operating times, by default over 5 years with single set of batteries.

Modern and completely wireless: Members of the Aistin family never require a separate gateway. The device is connected to the internet via 4G NB-IoT.



Optionally available with an external antenna

Why Aistin

Modern, elegant, functional

- Independent and Maintenance Free
- Completely Wireless — Over-the-air updates and Device Management
- Plug-and-Play – Functional, ready with software, ready to use
- Shock- and Waterproof, Robust*

Use Case Examples

Measure any surface level

- The fill level of fuel and water tanks
- The fill rate of waste bins or gravel storage
- The temperature and level of foodstuff
- Predictive alerts forward the need to refill or empty containers

iProtoxi Custom

All of our products and services can be tailored to connect to other cloud services and API interfaces or include additional features. For any tailoring related questions, please consult our sales at sales@iprotoxi.fi

TECHNICAL SPECIFICATION

Device Settings

Aistin Level is configurable **remotely over-the-air**. With **IoThund Cloud** web and mobile apps, all of the devices can be updated, configured, and managed at bulk or one at a time.

Inside the Casing

- ❑ **Connectivity: 4G Cat M1 & NB-IoT**
 - NFC 13.56 MHz
- ❑ **Dimensions:** 90 x 90 x 28,5 mm
 - IP67 casing
 - Weight 170 g
- ❑ **Operating temperature:**
 - -25 to +60 °C
 - -40 to 85 °C with reduced accuracy
- ❑ **Powering:** 1 x 3,6V C Primary battery
- ❑ **Battery lifetime:**

Over 5 years: 12 measurements / day

Battery lifetime is dependent on used features like positioning
- ❑ **Surface Distance Radar:**
 - Can detect multiple objects
 - 10° arc of the radar cone
 - Adjustable start distance: from 200 mm to 11900 mm
 - Maximum distance 12 meters
 - Distance and amplitude
 - Unaffected by dirt and rain
 - Accuracy ± 10 mm
- ❑ **NTC Temperature (Device Temperature)**

By default, the NTC is installed inside the casing, but may be fit into the casing seam to react quicker to changes in outer temperature.

 - Range from -40 to +125 °C
 - Accuracy ± 1 °C
- ❑ **Device Orientation:** 360°

Positioning

- ❑ **IoTrack (NB-IoT):**
 - Cellular positioning
 - Accuracy up to few 100 meters
- ❑ **Optional:** GPS/(GNSS)

Device Management

- ❑ **Measurement and Alarming Functions**
- ❑ **Complete Device Management and Firmware Updates:** Over-the-air via IoThund Cloud

Product Code

- ❑ **Order Numbers**
 - With SIM card 20021
 - No SIM card 20022
 - With SIM card and an External Antenna (50cm) 20221