

## Floorstanding WC rimless combination with cistern and seat and cover with fixing holes for floor fixation 82515.2



### TECHNICAL DATA

|                     |  |
|---------------------|--|
| Order no.           | 82515.2  |
| Certified to        | EN 997   |
| Specification       | Washdown for 4,5/3-l-flush, with shut-off valve, Charge 783<br>2 fixing holes<br>with cistern flushing mechanism,<br>water condensation insulation,<br>Dual-Flush (4,5/3-l-flush), water inlet bottom<br>right 1/2" brass<br>with seat and cover, Thermoplast, removable |
| Outlet              | horizontal<br>VARIO, vertical 70 - 250 mm  |
| Weight              | 35,0 kg  |
| Mounting acc. incl. | Fastening kit, order no. 89175.7   |

|                     |  |
|---------------------|--|
| Mounting acc. excl. | for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2<br>for VARIO-outlet 160 - 250 mm only LAUFEN-connection, order no. 89902.5 |
| Colours             | see colour table   |

### SPECIFICATION TEXT

Floorstanding WC rimless washdown Laufen-KOMPAS, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush), with seat and cover, Thermoplast, removable EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 850 mm outlet horizontal, VARIO vertical 70 - 250 mm back to wall, concealed fixation, 2 fixing holes  
Special feature: rimless, concealed surfaces directing water are fully glazed throughout, vacuum checked  
Further options: Surface refinement LCC  
Order no. 82515.2

### TECHNICAL DRAWINGS / S 1 : 20

