


PE ELGEF® Plus



Elektrosvets-T-rör 90°

- PE 100 SDR 11 (ISO S5)
- 10 bar gas / 16 bar vatten
- 4 mm Stift
- Material-utflödesbegränsade svetsindikatorer för god visuell kontroll
- Två separata svetszoner




d [mm]	Beställningsnr.	RSK	SP	kg	d1 [mm]	L [mm]	L1 [mm]	z [mm]	z1 [mm]	H [mm]	
200	753 201 819	242 33 45	1	10,100	245	560	104	176	250	117	
225	753 201 820	242 33 46	1	15,145	274	610	112	193	270	122	
250	753 201 821	242 33 47	1	18,100	305	667	123	211	288	127	



Elektrosvets-T-rör 90° reducerat

- PE 100 SDR 11 (ISO S5)
- 10 bar gas / 16 bar vatten
- 4 mm Stift
- Material-utflödesbegränsade svetsindikatorer för god visuell kontroll
- Två separata svetszoner
- *genomgående svetszon




d [mm]	d2 [mm]	Beställningsnr.	RSK	SP	kg	d1 [mm]	L [mm]	L1 [mm]	z [mm]	z1 [mm]	H [mm]	
160	63	753 211 037	242 47 86	1	4,940	196	405	90	113	176	65	
160	90	753 211 039	242 47 87	1	5,040	196	405	90	113	188	79	
160	110	753 211 040	242 47 88	1	5,160	196	405	90	113	195	85	
200	90	753 211 059	242 47 89	1	11,260	245	557	104	175	215	81	
200	110	753 211 060	242 47 90	0	11,260	245	557	104	175	218	84	
200	160	753 211 063	242 47 91	0	11,260	245	557	104	175	236	101	
225	90	753 211 069	242 47 92	1	12,700	274	615	112	196	226	80	
225	110	753 211 070	242 47 93	1	12,750	274	615	112	196	235	85	
225	160	753 211 073	242 47 94	1	13,200	274	615	112	196	255	105	
250	110	753 211 080	242 47 95	0	11,260	305	668	123	211	245	85	
250	160	753 211 083	242 47 96	0	11,260	305	668	123	211	264	101	



Elektrosvets-förminskning med integrerad rörfixtur

- PE 100 SDR 11 (ISO S5)
- 10 bar gas / 16 bar vatten
- 4 mm Stift
- Material-utflödesbegränsade svetsindikatorer för god visuell kontroll



d [mm]	d2 [mm]	Beställningsnr.	RSK	SP	kg	d1 [mm]	L [mm]	L1 [mm]	L2 [mm]	z [mm]	H [mm]	
25	20	753 901 639	242 30 23	20	0,059	35	74	34	34	6		
32	20	753 901 640	242 28 11	1	0,071	44	79	33	36	10		
32	25	753 901 641	242 28 12	1	0,060	44	79	33	36	10		
40	32	753 901 646	242 29 42	1	0,072	54	88	33	39	13		
50	32	753 901 651	242 28 13	1	0,096	66	96	35	43	18		
50	40	753 901 652	242 28 14	1	0,136	66	96	39	43	14		
63	32	753 901 656	242 28 15	1	0,171	81	106	35	48	23		
63	40	753 901 657	242 28 16	1	0,176	81	106	39	48	19		
63	50	753 901 658	242 28 17	1	0,189	81	106	43	48	15		