

**PN 16/25**

KAT-A 1943

Product characteristics and benefits

- Double function air valve
- Single chamber air valve in compact design
- For domestic water supply
- Venting function:
 - Small orifice to release low quantities of air during operation under pressure
 - Small orifice to vent low quantities of air
- For discharge of small quantities of air
- For venting of small quantities of air
- With female thread for easy screwing onto the pipeline
- Outlet female threaded acc. to DIN ISO 228 G ¾", G 1", G 1 ¼"
- Minimum operation pressure: 0.5 bar

Materials

- Body: Ductile iron EN-GJS-400-15 (GGG-40)
- Bonnet: Ductile iron EN-GJS-400-15 (GGG-40)
- Bonnet bolts: Stainless steel A2 (DIN EN ISO 3506)
- Float: Plastic polypropylene
- Sealing: NBR

Corrosion protection

- Internally and externally epoxy coated acc. to GSK guidelines

Versions

- Standard version as described
- With ball valve
- Flanged versions of sizes DN 25, 32, 40 & 50 on request

Field of application

- Chamber installation
- Installation in plants

Tests and approvals

- Final inspection test according to EN 12266-1 (leakage rate A)

Without ball valve



With ball valve

**Note**


For proper installation and safe operation please follow the installation and operation instructions:
KAT-B 1943

Field of application

PN	Maximum operating pressure [bar]	Maximum operating temperature for neutral liquids [°C]
25	25	50
16	16	50



Drawing



*1: Ball valve as an option (not included in standard version)

Technical data

PN 16

G Screw connection [inch]	1"	1 1/4"	3/4"
Weight without ball valve approx. [kg]	4.5	4.5	4.5
Volume without ball valve approx. [m³]	0.003	0.003	0.003

Flanged versions of sizes DN 25, 32, 40 & 50 on request

PN 25


G Screw connection [inch]	1"	1 1/4"	3/4"
Weight without ball valve approx. [kg]	4.5	4.5	4.5
Volume without ball valve approx. [m³]	0.003	0.003	0.003

Flanged versions of sizes DN 25, 32, 40 & 50 on request



Further information

Rate of air release at full internal operating pressure



x: Operating pressure p in pipeline [bar]
y: Air release rate Q [m³/h]