

Environmental Product Declaration



In accordance with ISO 14025:2006 and EN 15804:2012+A2:2019/AC:2021 for:

Alterna showerhead / Alterna duschhuvud

from

Saint-Gobain Distribution Sweden AB



| | |
|--------------------------|--|
| Program: | The International EPD System, www.environdec.com |
| Program operator: | EPD International AB |
| Type of EPD: | EPD on multiple products, based on a representative product |
| EPD registration number: | EPD-IES-0025629:001 |
| Version date: | 2025-09-25 |
| Validity date: | 2030-09-24 |

An EPD may be updated or depublished if conditions change. To find the latest version of the EPD and to confirm its validity, see www.environdec.com



General information

Programme information

| | |
|-------------------|---|
| Programme: | The International EPD System |
| Address: | EPD International AB Box 210 60 SE-100 31 Stockholm Sweden |
| Website: | www.environdec.com |
| E-mail: | support@environdec.com |

PCR and verification

| |
|--|
| Product Category Rules (PCR): |
| CEN standard EN 15804:2012+A2:2019/AC:2021 serves as the Core Product Category Rules (PCR) |
| Product Category Rules (PCR): Construction Products PCR 2019:14 version 2.0.1 |
| PCR review was conducted by: PCR review was conducted by the Technical Committee of the International EPD® System. See https://environdec.com/about-us/the-international-epd-system-about-the-system for a list of members. Review chair: Rob Rouwette. The review panel may be contacted via the Secretariat www.environdec.com/contact . |
| Life Cycle Assessment (LCA) |
| LCA accountability: Fanni Véghvári, CarbonZero AB |
| Third-party verification |
| Independent third-party verification of the declaration and data, according to ISO 14025:2006, via: |
| <input checked="" type="checkbox"/> Individual EPD verification without a pre-verified LCA/EPD tool |
| Third-party verifier: Stephen Forson, ViridisPride |
| Approved by: The International EPD System |
| Procedure for follow-up of data during EPD validity involves third party verifier: |
| <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No |

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but published in different EPD programmes, may not be comparable. For two EPDs to be comparable, they shall be based on the same PCR (including the same first-digit version number) or be based on fully aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have identical scope in terms of included life-cycle stages (unless the excluded life-cycle stage is demonstrated to be insignificant); apply identical impact assessment methods (including the same version of characterisation factors); and be valid at the time of comparison.

For further information about comparability, see EN 15804 and ISO 14025.

Information about EPD owner

| | |
|--|---|
| Owner of the EPD | Saint-Gobain Distribution Sweden AB Bryggerivägen 9 168 67 Bromma Stockholm |
| Contact | SGDS - Beriar Maroof (beriar.maroof@saint-gobain.se) |
| Description of the organisation | <p>Saint-Gobain Distribution Sweden AB - specialists in collaboration for more efficient business in construction and installation. Saint-Gobain Distribution Sweden AB is the head company of some of Sweden's leading trading companies in construction, sheet metal, tiles and installation. All the companies have long and solid industry experience and provide most of Sweden's craftsmen with materials for various projects. Customers in different companies can also buy support items from the sister companies in the group, and in selected cases, we take joint projects to facilitate the logistics of the supply of goods, which is then often critical for a smooth construction project.</p> <ul style="list-style-type: none"> • Optimera - construction trade for professional carpenters • Dahl – heat, plumbing and sanitary specialist • Bevego - building sheet metal, ventilation and technical insulation • Kakelspecialisten and Konradsson's Tiles - tiles, tiling and bathroom fittings |

The company's focus is on sales and services with direct contact to about 150,000 customers regularly.




Saint-Gobain Distribution Sweden AB is owned by Saint-Gobain with a presence in 64 countries and over 190 000 employees worldwide.



Product information

| | |
|------------------------------------|--|
| Product name | Alterna showerhead / Alterna duschhuvud |
| Product identification | Shower articles |
| UN CPC code | 42911– Sinks, wash-basins, baths and other sanitary ware and parts thereof, of iron, steel, copper or aluminium |
| Product description | Alterna showerhead in different shapes and sizes |
| Location of production site | Xiamen, China |
| Technical data | Alterna showerhead, different sizes and colors. The showerheads are round with a diameter that ranges between 200 – 230 mm. For more technical specifications, please visit https://www.dahl.se/ or https://www.bd.dk/ |
| Use | Showerheads for personal hygiene |

Products included in this study

| Product name | Geographical scope | Article number | Product image | Website |
|--|--------------------|----------------|--|---|
| TAKDUSCHSIL DUCHA II 200 MM ALTERNA | Sweden | 8180557 |  | https://www.dahl.se/ |
| TAKDUSCHSIL DUCHA IV 200 MM ALTERNA | | 8180558 |  | |
| Alterna Image Hovedbruser Ø230 1-Jet Rain, silikonedyser på hele brusebunden. Krom, hvid bund | Denmark | 736978023 |  | https://www.bd.dk/ |

This EPD covers multiple products, with a representative product that was determined amongst the LCA practitioner, manufacturer and EPD owner. The EPD covers the products in the table above and as per the declared unit of 1 kg of product, the material composition and manufacturing processes are similar enough to assume that the environmental impact remains the same across all products. The representative product is bolded in the table.

Content declaration of representative product

| Product composition | Amount (kg) | Post-consumer recycled material, mass-% of product | Biogenic material, mass-% of product | Biogenic material ¹ , kg C/declared unit |
|-----------------------|-----------------|--|--|---|
| ABS | 8,90E-01 | 0 | 0 | 0 |
| EPDM | 1,50E-02 | 0 | 0 | 0 |
| NBR | 5,00E-04 | 0 | 0 | 0 |
| POM | 1,99E-02 | 0 | 0 | 0 |
| Stainless steel | 3,93E-02 | 0 | 0 | 0 |
| TPE | 3,53E-02 | 0 | 0 | 0 |
| Total | 1 | 0 | 0 | 0 |
| Packaging composition | Weight, kg | Weight-% (versus the product) | Biogenic material, mass-% of packaging | Biogenic material ¹ , kg C/declared unit |
| Cardboard | 9,00E-01 | 90 | 45 | 0,405 |
| PE | 1,00E-02 | 1 | 0 | 0 |
| PP | 1,70E-01 | 17 | 0 | 0 |
| Wood | 5,30E-01 | 53 | 47,2 | 0,250 |
| Total | 1,61E+00 | 161 | 41 | 0,655 |


| Hazardous substances from the candidate list of SVHC | EC No. | CAS No. | Mass-% per declared unit |
|--|--------|---------|--------------------------|
| - | - | - | - |

In this study, no hazardous or toxic materials or substances are included in the product that are in the candidate list of Substances of Very High Concern (SVHCs) which exceeds the limits for registration with the European Chemicals Agency (i.e., if the substance constitutes more than 0.1% of the weight of the product or any component of the product, if applicable).

¹ 1 kg biogenic carbon in the product/packaging is equal to 44/12 kg of CO₂ uptake

LCA information

| | |
|--|--|
| Declared unit | 1 kg of Alterna showerhead / Alterna duschhuvud |
| Reference service life | Not applicable as module B is not included |
| Technical lifespan | 50-60 years |
| Time representativeness | The data used to model product manufacturing correspond to 2024. The data from generic databases are from 2021 – 2024. No data used is older than 5 years. |
| Geographical scope | Modules A1-A2 are representative of China, A3 global and A4-A5, C1-C4 and D Denmark and Sweden |
| Database(s) and LCA software used | Calculation completed in LCA for Experts v10.9.1.19 with an integrated ecoinvent database 3.11 |
| System boundaries | Cradle to gate, with options (A1-A3, A4-A5, C1-C4 & D) |
| Process flow diagram | |



More information

The EPD covers showerheads with different shapes and colors. The product is sold in Sweden and Denmark.

A1, Raw material supply

This module considers the extraction and processing of all raw materials, energy, and transportation which occur upstream to the studied manufacturing process. The product mainly consists of plastics, rubbers and steel. Generic data has been used to model the production of the materials that make up the products.

A2, transport to the manufacturer

The raw materials are transported to the manufacturing site where the production takes place. Specific data from the manufacturers' suppliers has been considered.

A3, manufacturing

This module includes the assembly of Alterna showerhead / Alterna duschhuvud manufactured in China. During the production processes electricity, natural gas, steam and water are used. It is assumed that the inputs and outputs from this module are distributed equally across the products per declared unit as the processes are the same across all products. This module also includes the packaging materials which are used to transport the finished products to the distribution center. The packaging material consists of cardboard, PP and wood. Data has been collected by the manufacturer from the production year 2024, the full 12 months from January 2024 to December 2024. This module also includes the transportation between the manufacturing factory in China to Saint-Gobain distribution centers in Sweden and Denmark, which is calculated using Searates.

| Transportation type | Distance (km) |
|---------------------|---------------|
| Ship | 20 000 |
| Truck | 150 |

Electricity used in manufacturing:

The electricity used in the modelling is based on the energy mix of China from International Energy Agency (2023). The GWP-GHG values for the manufacturing stage impacts are 0,871 kg CO₂-eq./kWh.

A4, Transport

This stage includes transportation from Saint-Gobain's distribution centers out to the installation sites. The transportation distance to the installation sites is based on an average representative transportation of 350 km.

| Scenario information | Unit (expressed per declared unit) |
|---|--|
| Fuel type and consumption of vehicle or vehicle type used for transport e.g. long distance truck, boat etc. | Average truck trailer with a 27 t payload and 0,019 l/tkm diesel |
| Distance | 350 km |
| Capacity utilization (including empty returns) | 61% for truck |
| Volume capacity utilization factor (factor: =1 or <1 or 1 for compressed or nested packaged products | Not applicable |

A5, Construction installation

It has been assumed that the installation is done by hand and therefore has negligible impact. This stage also includes the waste management of the packaging that arises on the installation site. The waste rates of the different packaging materials are based on Swedish Statistics (SCB, 2020) as the waste management occurs in Sweden.

| Material | Recycling (%) | Incineration (%) | Landfill (%) |
|-------------------|---------------|------------------|--------------|
| Biogenic material | 0 | 100 | 0 |
| Plastic | 26 | 74 | 0 |

B1-B7 Use stage

This stage is not declared.

C1 Deconstruction/Demolition

This stage includes the de-construction of Alterna showerhead / Alterna duschhuvud. It is assumed that the deconstruction is done manually and therefore has a negligible impact.

C2 Transport

This module represents the transport distance to the waste processing facility. It is assumed that the transportation distance to the waste processing facility is 50 km.

C3 Waste processing

This module includes any waste treatment needed from recycling and incineration.

C4 Final disposal

This module includes any material that is landfilled.

| Processes | Unit (expressed per declared unit) |
|---|---|
| Collection process specified by type | 1 kg collected |
| | 0 kg collected with mixed construction waste |
| Recovery system specified by type | 0 kg for re-use |
| | 0,287 kg for recycling |
| | 0,711 kg for energy recovery |
| Disposal specified by type | 0,002 kg product or material for final deposition |
| Assumptions for scenario development, e.g. transportation | The transportation is modelled with an average truck trailer with a 27 t payload and 0,019 t/km |

100% scenarios

In addition to the most probable end-of-life stage scenario, 100% scenarios have been modelled to give other perspectives. As the most probable end-of-life scenario is based on Swedish statistics (which is similar to Danish statistics), this information can be used to calculate another end-of-life scenario. The 100% scenarios have been modelled in accordance with the default values given in table 4 of PCR2019:14 Version 2.0, to complement other processes in the end-of-life stage. Values for the end-of-life stage for the 100% scenarios are described in the table below.

| Module | Processes | Energy carrier | Quantity [kWh/tonne] | Weight considered [kg] |
|--------|--|----------------|------------------------|------------------------|
| C1 | Demolition/deconstruction of concrete/reinforced concrete | Diesel | 10 | 0 |
| | Demolition/deconstruction of masonry, tiles and paver blocks | Diesel | 5 | 0 |
| | Demolition/deconstruction of steel, wood and other materials | Diesel | 1.1 | 1 |
| Module | Processes | Distance [km] | Weight considered [kg] | |
| C2 | Transports (for materials not to be incinerated) | 80 | 0,131 | |
| | Transports (for materials to be incinerated) | 130 | 0,869 | |
| Module | Processes | Energy carrier | Quantity [kWh/tonne] | Weight considered [kg] |
| C3 | Loading and unloading at sorting facility | Diesel | 1.8 | 1 |
| | Mechanical sorting | Electricity | 2.2 | 1 |
| | Crushing of concrete | Diesel | 2.0 | 0 |
| | Crushing of masonry, tiles and paver blocks | Diesel | 1.5 | 0 |
| | Fragging of steel | Diesel | 7.4 | 0,037 |
| | Chipping of wood | Diesel | 6.0 | 0 |
| | Treatment of other materials | Diesel | 0.8 | 0,961 |
| C4 | Compacting of inert construction waste for landfills (including backfilling) | Diesel | 1.6 | 0,002 |

D Benefits and loads beyond the system boundary

This module includes loads and benefits obtained from energy recovery and/or recycling materials.

Omissions of life cycle stages

The following flows were excluded from the system boundary:

- **A1-A3:** The plants, production of machines and transportation systems are excluded since the related flows are supposed to be negligible compared to the potential environmental impacts through the life cycle of the product
- **B1-B7:** The use phase of the products is not included

In addition, the following flows are excluded from the system boundaries:

- Flows related to human activities, such as employee transport

Cut-off criteria

The following procedures were followed for the exclusion of inputs and output.

- All input and output flows in a unit process were considered i.e., taking into account the value of all flows in the unit process and the corresponding LCI where data was available
- Data gaps were filled by conservative assumptions with average or generic data. Any assumptions in such cases were documented
- The use of cut-off criterion on mass inputs and primary energy at the unit process level (1%) and at the information module level (5%)

All hazardous and toxic materials and substances are included in the inventory, and the cut-off rules do not apply.

Allocation

Allocation criteria are based on mass.

Modules declared and geographical scope

| | Product stage | | | Assembly stage | | Use stage | | | | | | | End of life stage | | | | Benefits & loads beyond system boundary |
|--------------------|---------------|-----------|---------------|----------------|----------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|---|
| | Raw materials | Transport | Manufacturing | Transport | Assembly | Use | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery-Recycling-potential |
| Modules | A1 | A2 | A3 | A4 | A5 | B1 | B2 | B3 | B4 | B5 | B6 | B7 | C1 | C2 | C3 | C4 | D |
| Modules declared | X | X | X | X | X | ND | ND | ND | ND | ND | ND | ND | X | X | X | X | X |
| Geography | CN | CN | CN | DK & SE | DK & SE | - | - | - | - | - | - | - | DK & SE | DK & SE | DK & SE | DK & SE | DK & SE |
| Specific data used | 47,1%* | | | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Variation products | <10% | | | - | - | - | - | - | - | - | - | - | - | - | - | - | - |
| Variation sites | 0% | | | - | - | - | - | - | - | - | - | - | - | - | - | - | - |

*The specific data is based on the amount of impact that derives from the impact indicator GWP-GHG for modules A1-A3.

Declaration of data sources, reference years, and share of primary data:

| Process | Source type | Source | Reference year | Data category | Share of primary data, of GWP-GHG results for A1-A3 |
|---|----------------|----------------------------|----------------|---|---|
| Manufacturing of product | Collected data | EPD owner | 2021-2024 | Primary data | 2% |
| Transport of components to production site | Collected data | EPD owner , ecoinvent 3.11 | 2021-2022 | Primary data | 0,1% |
| Transport of product to SGDS | Collected data | EPD owner, ecoinvent 3.11 | 2021-2022 | Primary data | 45% |
| Production of components | Database | ecoinvent v3.11, Shpera | 2010-2024 | Representative generic data | 0% |
| Production of packaging | Database | ecoinvent v3.11, Shpera | 2021-2024 | Representative generic data | 0% |
| Other processes | Database | ecoinvent v3.11, Shpera | 2021-2024 | Representative generic data, proxy data | 0% |
| Total share of primary data, of GWP-GHG results for A1-A3 | 47,1% | | | | |

Summary of data quality:

The data quality detailed above is considered being fair as majority of the data has been collected by the manufacturer, but the datasets used represent a fair geographical scope due to unavailable datasets. As majority of that data has the largest contribution to the climate impact of the products, the data quality has been deemed fair.

Environmental Performance

The estimated impact results are only relative statements, which do not indicate the endpoints of the impact categories, exceeding threshold values, safety margins and/or risks. As module C is included in the EPD, it is discouraging the use of the results of modules A1-A3 without considering the results of module C.

Mandatory impact category indicators according to EN 15804, EF 3.1

| Results per declared unit: 1 kg | | | | | | | | | |
|------------------------------------|---|-----------|----------|----------|----------|----------|----------|----------|-----------|
| Indicator | Unit | A1-A3 | A4 | A5 | C1 | C2 | C3 | C4 | D |
| GWP-total | kg CO ₂ eq | 5,60E+00 | 7,20E-02 | 2,85E+00 | 3,62E-04 | 1,31E-02 | 5,66E-02 | 2,23E+00 | -1,32E+00 |
| GWP-fossil | kg CO ₂ eq | 7,86E+00 | 7,11E-02 | 4,48E-01 | 3,62E-04 | 1,29E-02 | 5,22E-02 | 2,23E+00 | -1,28E+00 |
| GWP-biogenic | kg CO ₂ eq | -2,27E+00 | 1,70E-04 | 2,40E+00 | 4,02E-08 | 3,09E-05 | 4,38E-03 | 7,47E-05 | -2,37E-02 |
| GWP-luluc | kg CO ₂ eq | 8,83E-03 | 7,29E-04 | 7,45E-05 | 3,71E-08 | 1,32E-04 | 5,01E-05 | 1,90E-05 | -1,88E-02 |
| ODP | kg CFC-11 eq | 6,62E-08 | 1,18E-14 | 9,90E-11 | 5,38E-12 | 2,33E-15 | 5,70E-10 | 1,29E-13 | -4,82E-12 |
| AP | mole H ⁺ eq | 7,48E-02 | 1,54E-04 | 5,76E-04 | 3,24E-06 | 8,55E-05 | 2,00E-04 | 2,24E-04 | -1,20E-03 |
| EP-freshwater | kg P eq | 1,01E-03 | 1,91E-07 | 1,90E-06 | 1,17E-08 | 3,45E-08 | 1,05E-05 | 1,52E-08 | -1,88E-06 |
| EP-marine | kg N eq | 1,86E-02 | 6,79E-05 | 1,99E-04 | 1,51E-06 | 4,22E-05 | 9,75E-05 | 4,82E-05 | -3,95E-04 |
| EP-terrestrial | mole N eq | 1,82E-01 | 7,29E-04 | 2,54E-03 | 1,65E-05 | 4,61E-04 | 6,75E-04 | 1,06E-03 | -4,42E-03 |
| POCP | kg NMVOC eq | 5,50E-02 | 1,39E-04 | 5,30E-04 | 4,94E-06 | 8,13E-05 | 2,45E-04 | 1,43E-04 | -1,04E-03 |
| ADP-minerals & metals ² | kg Sb eq | 1,04E-05 | 4,71E-09 | 5,12E-08 | 1,29E-10 | 8,54E-10 | 2,70E-07 | 1,40E-09 | -4,59E-07 |
| ADP-fossil ² | MJ | 1,44E+02 | 9,07E-01 | 7,70E-01 | 4,67E-03 | 1,65E-01 | 6,53E-01 | 2,62E-01 | -2,83E+01 |
| WDP ² | m ³ | 3,40E+00 | 3,24E-04 | 2,91E-01 | 1,43E-05 | 6,08E-05 | 1,13E-02 | 2,05E-01 | -1,03E-01 |
| Acronyms | GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption | | | | | | | | |

² The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator

Resource use indicators

| Results per declared unit: 1 kg | | | | | | | | | |
|---------------------------------|--|----------|----------|-----------|----------|----------|----------|-----------|-----------|
| Indicator | Unit | A1-A3 | A4 | A5 | C1 | C2 | C3 | C4 | D |
| PERE | MJ | 2,92E+01 | 6,84E-02 | 1,78E-01 | 2,97E-05 | 1,25E-02 | 4,25E-02 | 7,19E-02 | -1,25E+01 |
| PERM | MJ | 2,68E+01 | 0,00E+00 | -2,68E+01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| PERT | MJ | 5,60E+01 | 6,84E-02 | -2,66E+01 | 2,97E-05 | 1,25E-02 | 4,25E-02 | 7,19E-02 | -1,25E+01 |
| PENRE | MJ | 1,44E+02 | 9,07E-01 | 7,70E-01 | 4,67E-03 | 1,65E-01 | 6,53E-01 | 2,62E-01 | -2,83E+01 |
| PENRM | MJ | 4,54E+01 | 0,00E+00 | -8,35E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | -3,71E+01 | 0,00E+00 |
| PENRT | MJ | 1,89E+02 | 9,07E-01 | -7,58E+00 | 4,67E-03 | 1,65E-01 | 6,53E-01 | -3,68E+01 | -2,83E+01 |
| SM | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| RSF | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| NRSF | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| FW | m3 | 8,00E-02 | 3,38E-05 | 6,85E-03 | 3,33E-07 | 6,21E-06 | 2,68E-04 | 4,81E-03 | -2,22E-02 |
| Acronyms | PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water | | | | | | | | |

Additional mandatory and voluntary impact category indicators

| Results per declared unit: 1 kg | | | | | | | | | |
|---------------------------------|---|----------|----------|----------|----------|----------|----------|----------|-----------|
| Indicator | Unit | A1-A3 | A4 | A5 | C1 | C2 | C3 | C4 | D |
| GWP-GHG ³ | kg CO2 eq | 7,99E+00 | 7,19E-02 | 4,49E-01 | 3,62E-04 | 1,30E-02 | 5,63E-02 | 2,23E+00 | -1,32E+00 |
| Acronyms | GWP-GHG = global warming potential - greenhouse gases | | | | | | | | |

Waste indicators

| Results per declared unit: 1 kg | | | | | | | | | |
|---------------------------------|--|----------|----------|----------|----------|----------|----------|----------|-----------|
| Indicator | Unit | A1-A3 | A4 | A5 | C1 | C2 | C3 | C4 | D |
| HWD | kg | 1,87E-01 | 3,64E-11 | 6,35E-04 | 4,18E-06 | 6,83E-12 | 3,60E-03 | 3,79E-09 | -6,48E-08 |
| NHWD | kg | 2,17E+00 | 1,27E-04 | 7,45E-02 | 3,10E-05 | 2,31E-05 | 9,01E-02 | 1,97E-03 | -4,56E-02 |
| RWD | kg | 1,03E-04 | 1,71E-06 | 3,43E-05 | 0,00E+00 | 3,38E-07 | 2,23E-06 | 1,50E-05 | -3,20E-03 |
| Acronyms | HW = Hazardous waste disposed; NHW = Non-hazardous waste disposed; RW = Radioactive waste disposed | | | | | | | | |

³ This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic CO2 is set to zero

Output flow indicators

| Results per declared unit: 1 kg | | | | | | | | | |
|---------------------------------|---|----------|----------|----------|----------|----------|----------|----------|----------|
| Indicator | Unit | A1-A3 | A4 | A5 | C1 | C2 | C3 | C4 | D |
| CRU | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| MFR | kg | 6,11E-04 | 0,00E+00 | 4,42E-02 | 0,00E+00 | 0,00E+00 | 2,87E-01 | 0,00E+00 | 0,00E+00 |
| MER | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| EEE | MJ | 0,00E+00 | 0,00E+00 | 3,97E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 4,75E+00 | 0,00E+00 |
| EET | MJ | 0,00E+00 | 0,00E+00 | 7,16E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 8,45E+00 | 0,00E+00 |
| Acronyms | CRU = Components for reuse; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electric energy; ETE = Exported thermal energy | | | | | | | | |

Information on biogenic carbon content

| Biogenic carbon content | Unit per declared unit | Amount |
|--------------------------------------|------------------------|----------|
| Biogenic carbon content in product | kg C | 0,00E+00 |
| Biogenic carbon content in packaging | kg C | 6,55E-01 |

1 kg biogenic carbon is equivalent to 44/12 kg CO₂.

Additional Environmental Information

In addition to the most probable scenario, results from the corresponding 100% scenarios are added in this section.

Mandatory impact category indicators according to EN 15804, EF 3.1

| Results per declared unit: 1 kg | | | | | | | | | | | | | | |
|------------------------------------|---|----------|------------|-------------|------------|------------|-------------|------------|------------|-------------|------------|-----------|------------|-----------|
| Indicator | Unit | C1 100% | C2 100% RC | C2 100% INC | C2 100% LF | C3 100% RC | C3 100% INC | C3 100% LD | C4 100% RC | C4 100% INC | C4 100% LF | D 100% RC | D 100% INC | D 100% LF |
| GWP-total | kg CO ₂ eq | 3,62E-04 | 1,27E-02 | 1,22E-02 | 4,99E-04 | 2,18E-01 | 3,01E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 8,43E-04 | -3,93E-01 | -8,49E-01 | 0,00E+00 |
| GWP-fossil | kg CO ₂ eq | 3,62E-04 | 1,28E-02 | 1,23E-02 | 5,05E-04 | 1,97E-01 | 3,01E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 8,42E-04 | -3,91E-01 | -8,20E-01 | 0,00E+00 |
| GWP-biogenic | kg CO ₂ eq | 7,34E-08 | -2,83E-04 | -2,72E-04 | -1,11E-05 | 2,08E-02 | 9,75E-05 | 0,00E+00 | 0,00E+00 | 0,00E+00 | -1,18E-06 | -2,19E-03 | -1,54E-02 | 0,00E+00 |
| GWP-luluc | kg CO ₂ eq | 3,71E-08 | 1,32E-04 | 1,27E-04 | 5,18E-06 | 1,86E-04 | 2,77E-05 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 2,63E-06 | -6,65E-04 | -1,37E-02 | 0,00E+00 |
| ODP | kg CFC-11 eq | 5,38E-12 | 2,12E-15 | 2,04E-15 | 8,35E-17 | 2,16E-09 | 1,06E-11 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 9,67E-14 | -4,31E-12 | -2,62E-12 | 0,00E+00 |
| AP | mole H ⁺ eq | 3,24E-06 | 8,44E-05 | 8,11E-05 | 3,32E-06 | 7,43E-04 | 3,10E-04 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 5,27E-06 | -6,62E-04 | -6,58E-04 | 0,00E+00 |
| EP-freshwater | kg P eq | 1,17E-08 | 3,45E-08 | 3,31E-08 | 1,36E-09 | 4,02E-05 | 4,46E-08 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,39E-09 | -2,79E-06 | -7,51E-07 | 0,00E+00 |
| EP-marine | kg N eq | 1,51E-06 | 4,20E-05 | 4,03E-05 | 1,65E-06 | 3,64E-04 | 6,83E-05 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,30E-06 | -1,53E-04 | -2,43E-04 | 0,00E+00 |
| EP-terrestrial | mole N eq | 1,65E-05 | 4,58E-04 | 4,40E-04 | 1,80E-05 | 2,48E-03 | 1,47E-03 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,41E-05 | -1,65E-03 | -2,76E-03 | 0,00E+00 |
| POCP | kg NMVOC eq | 4,94E-06 | 8,05E-05 | 7,74E-05 | 3,16E-06 | 9,07E-04 | 2,03E-04 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 4,03E-06 | -4,29E-04 | -6,19E-04 | 0,00E+00 |
| ADP-minerals & metals ⁴ | kg Sb eq | 1,29E-10 | 8,51E-10 | 8,18E-10 | 3,35E-11 | 1,04E-06 | 2,28E-09 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 5,90E-11 | -4,57E-07 | -5,57E-08 | 0,00E+00 |
| ADP-fossil ² | MJ | 4,67E-03 | 1,64E-01 | 1,58E-01 | 6,45E-03 | 2,44E+00 | 3,76E-01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,37E-02 | -5,18E+00 | -1,93E+01 | 0,00E+00 |
| WDP ² | m ³ | 1,43E-05 | 5,85E-05 | 5,62E-05 | 2,30E-06 | 4,31E-02 | 2,78E-01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 9,79E-05 | -6,46E-02 | -5,93E-02 | 0,00E+00 |
| Acronyms | GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption | | | | | | | | | | | | | |

⁴ The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator

Resource use indicators

| Results per declared unit: 1 kg | | | | | | | | | | | | | | |
|---------------------------------|--|----------|------------|-------------|------------|------------|-------------|------------|------------|-------------|------------|-----------|------------|-----------|
| Indicator | Unit | C1 100% | C2 100% RC | C2 100% INC | C2 100% LF | C3 100% RC | C3 100% INC | C3 100% LD | C4 100% RC | C4 100% INC | C4 100% LF | D 100% RC | D 100% INC | D 100% LF |
| PERE | MJ | 2,97E-05 | 1,24E-02 | 1,19E-02 | 4,86E-04 | 1,36E-01 | 1,06E-01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 2,23E-03 | -2,67E+00 | -8,58E+00 | 0,00E+00 |
| PERM | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| PERT | MJ | 2,97E-05 | 1,24E-02 | 1,19E-02 | 4,86E-04 | 1,36E-01 | 1,06E-01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 2,23E-03 | -2,67E+00 | -8,58E+00 | 0,00E+00 |
| PENRE | MJ | 4,67E-03 | 1,64E-01 | 1,58E-01 | 6,45E-03 | 2,44E+00 | 3,76E-01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,37E-02 | -5,18E+00 | -1,93E+01 | 0,00E+00 |
| PENRM | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| PENRT | MJ | 4,67E-03 | 1,64E-01 | 1,58E-01 | 6,45E-03 | 2,44E+00 | 3,76E-01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,37E-02 | -5,18E+00 | -1,93E+01 | 0,00E+00 |
| SM | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| RSF | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| NRSF | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| FW | m3 | 3,33E-07 | 6,11E-06 | 5,87E-06 | 2,40E-07 | 1,01E-03 | 6,51E-03 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 2,88E-06 | -9,13E-03 | -1,11E-02 | 0,00E+00 |
| Acronyms | PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water | | | | | | | | | | | | | |

Additional mandatory and voluntary impact category indicators

| Results per declared unit: 1 kg | | | | | | | | | | | | | | |
|---------------------------------|---|----------|------------|-------------|------------|------------|-------------|------------|------------|-------------|------------|-----------|------------|-----------|
| Indicator | Unit | C1 100% | C2 100% RC | C2 100% INC | C2 100% LF | C3 100% RC | C3 100% INC | C3 100% LD | C4 100% RC | C4 100% INC | C4 100% LF | D 100% RC | D 100% INC | D 100% LF |
| GWP-GHG ⁵ | kg CO2 eq | 3,62E-04 | 1,30E-02 | 1,25E-02 | 5,11E-04 | 2,12E-01 | 3,01E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 8,47E-04 | -3,93E-01 | -8,49E-01 | 0,00E+00 |
| Acronyms | GWP-GHG = global warming potential - greenhouse gases | | | | | | | | | | | | | |

Waste indicators

| Results per declared unit: 1 kg | | | | | | | | | | | | | | |
|---------------------------------|--|----------|------------|-------------|------------|------------|-------------|------------|------------|-------------|------------|-----------|------------|-----------|
| Indicator | Unit | C1 100% | C2 100% RC | C2 100% INC | C2 100% LF | C3 100% RC | C3 100% INC | C3 100% LD | C4 100% RC | C4 100% INC | C4 100% LF | D 100% RC | D 100% INC | D 100% LF |
| HWD | kg | 4,18E-06 | 6,58E-12 | 6,32E-12 | 2,59E-13 | 1,38E-02 | 8,12E-06 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 7,30E-08 | -1,43E-07 | -1,31E-08 | 0,00E+00 |
| NHWD | kg | 3,10E-05 | 2,29E-05 | 2,20E-05 | 9,00E-07 | 3,46E-01 | 1,20E-02 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,00E+00 | -1,13E-01 | -1,19E-02 | 0,00E+00 |
| RWD | kg | 0,00E+00 | 3,10E-07 | 2,97E-07 | 1,22E-08 | 2,24E-06 | 2,24E-05 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,89E-07 | -6,18E-04 | -2,22E-03 | 0,00E+00 |
| Acronyms | HW = Hazardous waste disposed; NHW = Non-hazardous waste disposed; RW = Radioactive waste disposed | | | | | | | | | | | | | |

⁵ This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic CO2 is set to zero

Output flow indicators

| Results per declared unit: 1 kg | | | | | | | | | | | | | | |
|---------------------------------|---|----------|------------|-------------|------------|------------|-------------|------------|------------|-------------|------------|-----------|------------|-----------|
| Indicator | Unit | C1 100% | C2 100% RC | C2 100% INC | C2 100% LF | C3 100% RC | C3 100% INC | C3 100% LD | C4 100% RC | C4 100% INC | C4 100% LF | D 100% RC | D 100% INC | D 100% LF |
| CRU | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| MFR | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| MER | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| EEE | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 6,42E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| EET | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,14E+01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
| Acronyms | CRU = Components for reuse; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electric energy; ETE = Exported thermal energy | | | | | | | | | | | | | |


Disclaimers

| ILCD classification | Indicator | Disclaimer |
|---|---|------------|
| ILCD Type 1 | Global warming potential (GWP) | None |
| | Depletion potential of the stratospheric ozone layer (ODP) | None |
| | Potential incidence of disease due to PM emissions (PM) | None |
| ILCD Type 2 | Acidification potential, Accumulated Exceedance (AP) | None |
| | Eutrophication potential, Fraction of nutrients reaching freshwater end compartment (EP-freshwater) | None |
| | Eutrophication potential, Fraction of nutrients reaching marine end compartment (EP-marine) | None |
| | Eutrophication potential, Accumulated Exceedance (EP-terrestrial) | None |
| | Formation potential of tropospheric ozone (POCP) | None |
| | Potential Human exposure efficiency relative to U235 (IRP) | 1 |
| ILCD Type 3 | Abiotic depletion potential for non-fossil resources (ADP-minerals&metals) | 2 |
| | Abiotic depletion potential for fossil resources (ADP-fossil) | 2 |
| | Water (user) deprivation potential, deprivation-weighted | 2 |
| | Water consumption (WDP) | 2 |
| | Potential Comparative Toxic Unit for ecosystems (ETP-fw) | 2 |
| | Potential Comparative Toxic Unit for humans (HTP-c) | 2 |
| | Potential Comparative Toxic Unit for humans (HTP-nc) | 2 |
| | Potential Soil quality index (SQP) | 2 |
| <p>Disclaimer 1 – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.</p> <p>Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.</p> | | |

Additional information

Greenhouse gas emission from the use of electricity in the manufacturing phase.

| Residual mix | Unit | Value |
|--------------------|------------------------------|---|
| Location | | China – Fujian region |
| Electricity mix | | Biomass: 3,65% Hard coal: 60,60% Heavy Fuel Oil: 18,10% Hydro: 3,00% Natural gas: 8,00% Nuclear: 3,00% Photovoltaic: 1,83% Wind: 1,83% |
| Reference year | | 2023 |
| Source | | International Energy Agency |
| GWP excl. Biogenic | kg CO ₂ -eq. /kWh | 0,886 |



Abbreviations

| Abbreviation | Definition |
|------------------------------|--|
| General Abbreviations | |
| EN | European Norm (Standard) |
| EF | Environmental Footprint |
| GPI | General Programme Instructions |
| ISO | International Organization for Standardization |
| CEN | European Committee for Standardization |
| CPC | Central product classification |
| SVHC | Substances of Very High Concern |
| ND | Not Declared |
| CN | China |
| GLO | Global |
| DK | Denmark |
| SE | Sweden |




References

| | |
|-----------------------------|---|
| Dahl DK | Brødrene Dahl https://www.bd.dk/ |
| Dahl SE | Dahl https://www.dahl.se/ |
| Ecoinvent (2025) | Ecoinvent dataset version 3.11 (2025) |
| EN15804:2012+A2:AC/2021 | Sustainability of construction works – Environmental product declaration – Core rules for the product category of constructions products |
| EPD International (2024) | General Programme Instructions of the International EPD® System, version 5.0 |
| ISO 14020:2022 | International Standard ISO 14020 – Environmental statements and programmes for products – Principles and general requirements |
| ISO 14025:2006 | International Standard ISO 14025 – Environmental labels and declarations — Type III environmental declarations — Principles and procedures |
| ISO 14040:2006 | International Standard ISO 14040: Environmental Management – Life cycle assessment – Principles and framework. Second edition 2006-07-01. |
| ISO 14044:2006 | International Standard ISO 14044: Environmental Management – Life cycle assessment – Requirements and Guidelines |
| International Energy Agency | IEA (2023) China energy mix |
| PCR 2019:14 | Construction products v 2.0.1 |
| SCB (2020) | Treated waste by treatment category and waste category. Every second year 2010-2020. https://www.statistikdatabasen.scb.se/pxweb/sv/ssd/START_MI_MI0305/MI0305T003/ |
| Sphera (2025) | Sphera (2025) LCA for Experts. MLC database CUP 2024.02. |

Version history

Original Version of the EPD, 2025-09-25

Contact information

| | |
|-----------------------|---|
| EPD owner: |  Saint-Gobain Distribution Sweden Email: beriar.marroof@saint-gobain.se Telephone: +46 20 58 30 00 Address: Bryggerivägen 9, 168 67 Bromma, Sweden |
| LCA author: |  Fanni Végvári Email: fanni.vegvari@carbonzero.se Telephone: +46 73 854 90 52 Address: CarbonZero AB, Tåstrupsgatan 2, SE-262 32 Ångelholm, Sweden |
| Third party verifier: |  ViridisPride Ltd Stephen Forson Email: s.forson@viridispride.com |
| Program operator: |  INTERNATIONAL EPD SYSTEM EPD International AB info@environdec.com |

