



ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

Flush Plates



EPD HUB, EPD number HUB-5120

Published on 30.01.2026

Last updated on 30.01.2026

Valid until 29.01.2031

Life Cycle Assessment study has been performed in accordance with the requirements of EN 15804, EPD Hub PCR version 1.2 (24 Mar 2025) and JRC characterization factors EF 3.1.



Created with One Click LCA

LAUFEN

GENERAL INFORMATION

MANUFACTURER

Manufacturer	LAUFEN
Address	Wahlenstrasse 46, 4242 Laufen CH, Switzerland
Contact details	info@es.laufen.com
Website	www.laufen.com

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804:2012+A2:2019/AC:2021 and ISO 14025
PCR	EPD Hub Core PCR Version 1.2, 24 Mar 2025
Sector	Construction product
Category of EPD	Third party verified EPD
Parent EPD number	-
Scope of the EPD	Cradle to gate with modules C1-C4, D
EPD author	Elisa Pelaez (Sustainability Department, Roca Group)
EPD verification	Independent verification of this EPD and data, according to ISO 14025: o Internal verification p External verification
EPD verifier	Yazan Badour, as authorized verifier acting for EPD HUB Limited

This EPD is intended for business-to-business and/or business-to-consumer communication. The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products

may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT

Product name	Flush Plates
Additional labels	-
Product reference	-
Place(s) of raw material origin	Germany
Place of production	Germany
Place(s) of installation and use	Europe
Period for data	Calendar Year 2024
Averaging in EPD	Multiple products
Variation in GWP-fossil for A1-A3 (%)	-
GTIN (Global Trade Item Number)	-
NOBB (Norwegian Building Product Database)	-
A1-A3 Specific data (%)	0,68

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 Kg Flush plate
Declared unit mass	1 kg
Mass of packaging	0,647 kg
GWP-fossil, A1-A3 (kgCO₂e)	3,92
GWP-total, A1-A3 (kgCO₂e)	3,6
Secondary material, inputs (%)	1,78
Secondary material, outputs (%)	67,8
Total energy use, A1-A3 (kWh)	19,2
Net freshwater use, A1-A3 (m³)	0,08

PRODUCT AND MANUFACTURER

ABOUT THE MANUFACTURER

LAUFEN is dedicated to the production and sale of bathroom solutions that enrich people's everyday lives by creating unique spaces for wellbeing, personal care and health.

LAUFEN is the premium brand of Roca Group, a family-owned global enterprise driven by the Purpose of contributing to the well-being of society by delivering solutions that enhance everyday spaces, while caring for People and the Planet, and fostering Prosperity. Its commitment to sustainable development is deeply rooted in the organization—both as a strategic priority and through concrete actions. It is reflected in initiatives that translate this ambition into measurable improvements, ensuring that its day-to-day operations consistently contribute to a more positive and lasting impact.

Further information can be found at www.laufen.com and www.rocagroup.com

PRODUCT DESCRIPTION

This EPD covers flush plate products. The flush plate activates the toilet flushing mechanism and is installed together with the concealed cistern, secured by a mounting frame.

These products are mainly made of ABS.

To calculate the environmental impact, a representative average product based on the total volume manufactured in 2024 has been considered.

Further information can be found at: www.laufen.com

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass %	Material origin
Metals	0,83	EUROPE
Minerals	0	-
Fossil materials	99,17	EUROPE
Bio-based materials	0	-

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	0,019
Biogenic carbon content in packaging, kg C	0,112

FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 Kg Flush plate
Mass per declared unit	1 kg
Functional unit	-
Reference service life	-

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

PRODUCT LIFE-CYCLE

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Assembly stage		Use stage							End of life stage				Beyond the system boundaries		
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D		
x	x	x	ND	ND	ND	ND	ND	ND	ND	ND	ND	x	x	x	x	x		
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstruction/ demolition	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling

Modules not declared = ND. Modules not relevant = MNR

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, fuels used by machines, and handling of waste formed in the production processes at the manufacturing facilities are included in this stage. The study also considers the material losses occurring during the manufacturing processes as well as losses during electricity transmission.

A market-based approach is used in modelling the electricity mix utilized in the factory.

This EPD includes Flush plates products. These products are made of a mixture of fossil materials (ABS POM and TPE) and metals (stainless steel) being ABS the main component. ABS and POM materials are injected and then assembly process is carried out with the rest of components. The manufacturing process requires electricity for the different equipment. 100% of the electricity consumed in Rödental factory comes from renewable sources.

Transport from suppliers is calculated according to the corresponding sales volumes.

TRANSPORT AND INSTALLATION (A4-A5)

Module not declared.


PRODUCT USE AND MAINTENANCE (B1-B7)

Module not declared.

PRODUCT END OF LIFE (C1-C4, D)

Energy consumption and natural resources of the disassembling end-of-life product and the impacts of demolition process are assumed to be zero due to the negligible consumptions (C1). Concerning the end-of-life product, it is assumed to be sent to the closest waste disposal facility by lorry, estimated to be 50km away (C2). The product is suitable for reuse and recycling. The benefits and loads of recycling of the product and packaging waste are included in Module D.

SYSTEM DIAGRAM



LIFE-CYCLE ASSESSMENT

CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

The production of capital equipment, construction activities, and infrastructure, maintenance and operation of capital equipment, personnel-related activities, energy and water use related to company management and sales activities are excluded.

All industrial processes from raw material acquisition and pre-processing, production, product distribution and installation, and end-of-life management are included. Further, water used for cleaning, as well as production, transportation and waste streams of the packaging materials used for delivering the raw materials to the factory are omitted since the quantified mass contribution is less than 0.1%. The production of capital equipment, construction activities, and infrastructure, personnel-related activities, energy and water use related to company management and sales activities are excluded.

VALIDATION OF DATA

Data collection for production, transport, and packaging was conducted using time and site-specific information, as defined in the general information section on page 1 and 2. Upstream process calculations rely on generic data as defined in the Bibliography section. Manufacturer-provided specific and generic data were used for the product's manufacturing stage. The analysis

was performed in One Click LCA EPD Generator, with the 'Cut-Off, EN 15804+A2' allocation method, and characterization factors according to EN 15804:2012+A2:2019/AC:2021 and JRC EF 3.1.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging material	No allocation
Ancillary materials	No allocation
Manufacturing energy and waste	No allocation

PRODUCT & MANUFACTURING SITES GROUPING

Type of grouping	Multiple products
Grouping method	Based on a representative product
Variation in GWP-fossil for A1-A3, %	-

Primary data represents the manufacturing site of Rödental (Germany).

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator for EPD Hub V3 and EPD System Verification v3.2.3. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. The EPD Generator uses Ecoinvent v3.10.1/3.11 and One Click LCA databases as sources of environmental data. Allocation used in Ecoinvent 3.10.1/3.11 environmental data sources follow the methodology 'allocation, Cut-off, EN 15804+A2'.

ENVIRONMENTAL IMPACT DATA

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	3,50E+00	2,64E-02	8,02E-02	3,60E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,23E-02	2,22E+00	2,71E-01	-1,57E+00
GWP – fossil	kg CO ₂ e	3,42E+00	2,64E-02	4,67E-01	3,92E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,23E-02	1,36E+00	3,42E-02	-9,72E-01
GWP – biogenic	kg CO ₂ e	7,14E-02	3,36E-06	-4,07E-01	-3,35E-01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	1,32E-06	8,58E-01	2,36E-01	-6,04E-01
GWP – LULUC	kg CO ₂ e	9,35E-04	1,18E-05	1,95E-02	2,04E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	9,40E-06	4,00E-05	3,56E-06	1,52E-03
Ozone depletion pot.	kg CFC ₋₁₁ e	4,17E-06	3,92E-10	1,37E-08	4,19E-06	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	3,61E-10	3,97E-10	1,14E-10	-3,01E-08
Acidification potential	mol H ⁺ e	1,06E-02	8,98E-05	2,28E-03	1,30E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	7,44E-05	2,97E-04	3,70E-05	-4,43E-03
EP-freshwater ²⁾	kg Pe	2,67E-04	2,05E-06	2,67E-04	5,37E-04	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	1,67E-06	9,55E-06	1,52E-06	-7,79E-04
EP-marine	kg Ne	2,63E-03	2,95E-05	1,16E-03	3,82E-03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,46E-05	1,50E-04	1,80E-04	-1,03E-03
EP-terrestrial	mol Ne	2,64E-02	3,21E-04	7,90E-03	3,46E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,68E-04	1,29E-03	1,39E-04	-9,96E-03
POCP (“smog”) ³⁾	kg NMVOCe	8,16E-03	1,32E-04	2,12E-03	1,04E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	1,11E-04	3,38E-04	6,96E-05	-4,95E-03
ADP-minerals & metals ⁴⁾	kg Sbe	2,80E-06	7,38E-08	2,13E-06	5,00E-06	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	6,55E-08	2,85E-07	1,03E-08	-5,70E-06
ADP-fossil resources	MJ	9,01E+01	3,82E-01	7,19E+00	9,77E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	3,21E-01	3,69E-01	1,00E-01	-2,58E+01
Water use ⁵⁾	m ³ e depr.	9,04E-01	1,89E-03	3,00E-01	1,21E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	1,58E-03	4,49E-02	6,36E-04	-4,97E-02

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO₄e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	7,16E-08	2,63E-09	2,33E-08	9,75E-08	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,09E-09	2,66E-09	7,23E-10	-2,38E-08
Ionizing radiation ⁶⁾	kBq 11235e	8,58E-01	3,36E-04	5,35E-02	9,12E-01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	3,15E-04	2,21E-03	1,34E-04	-2,48E-01
Ecotoxicity (freshwater)	CTUe	1,54E+03	5,40E-02	1,62E+02	1,70E+03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	4,46E-02	4,87E-01	5,44E-01	-2,21E+00
Human toxicity, cancer	CTUh	1,01E-05	4,36E-12	4,30E-10	1,01E-05	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	3,72E-12	6,95E-11	2,89E-12	-1,61E-10
Human tox. non-cancer	CTUh	2,07E-06	2,47E-10	3,53E-09	2,07E-06	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,06E-10	2,69E-09	5,54E-10	-6,94E-09
SQP ⁷⁾	-	6,68E+00	3,82E-01	4,22E+01	4,92E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,85E-01	3,37E-01	2,23E-01	-5,10E+01

6) EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ	2,84E+00	5,27E-03	-5,62E-01	2,28E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	4,71E-03	-8,13E+00	-1,83E+00	-1,05E+01
Renew. PER as material	MJ	9,85E-03	0,00E+00	8,69E+00	8,70E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	-7,11E+00	-1,59E+00	5,41E+00
Total use of renew. PER	MJ	2,85E+00	5,27E-03	8,13E+00	1,10E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	4,71E-03	-1,52E+01	-3,43E+00	-5,08E+00
Non-re. PER as energy	MJ	5,92E+01	3,82E-01	7,03E+00	6,67E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	3,21E-01	-2,88E+01	-1,05E+01	-2,82E+01
Non-re. PER as material	MJ	3,32E+01	0,00E+00	2,88E-01	3,35E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	-2,45E+01	-9,06E+00	9,98E+00
Total use of non-re. PER	MJ	9,25E+01	3,82E-01	7,32E+00	1,00E+02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	3,21E-01	-5,33E+01	-1,96E+01	-1,82E+01
Secondary materials	kg	1,78E-02	1,63E-04	4,67E-01	4,85E-01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	1,40E-04	1,25E-03	3,54E-05	5,28E-01
Renew. secondary fuels	MJ	3,44E-02	2,07E-06	1,37E-01	1,71E-01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	1,77E-06	8,59E-06	6,53E-07	-3,68E-05
Non-ren. secondary fuels	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Use of net fresh water	m³	7,66E-02	5,64E-05	6,67E-03	8,33E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	4,62E-05	4,06E-04	-1,41E-03	-3,75E-03

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	3,96E-01	6,46E-04	2,89E-02	4,25E-01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	5,21E-04	1,61E-02	1,97E-04	-6,83E-02
Non-hazardous waste	kg	1,62E+00	1,20E-02	8,18E-01	2,45E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	9,98E-03	7,38E-01	1,90E+00	-6,49E+00
Radioactive waste	kg	6,47E-05	8,23E-08	1,37E-05	7,84E-05	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	7,74E-08	5,64E-07	3,27E-08	-6,37E-05

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Materials for recycling	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	6,78E-01	0,00E+00	0,00E+00
Materials for energy rec	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
Exported energy	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	6,64E+00	0,00E+00	0,00E+00
Exported energy – Electricity	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	2,79E+00	0,00E+00	0,00E+00
Exported energy – Heat	MJ	0,00E+00	0,00E+00	0,00E+00	0,00E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	0,00E+00	3,85E+00	0,00E+00	0,00E+00

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	3,32E+00	2,62E-02	4,91E-01	3,84E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,22E-02	1,37E+00	7,94E-02	-9,50E-01
Ozone depletion Pot.	kg CFC ₁₁ e	3,57E-06	3,13E-10	1,12E-08	3,58E-06	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,88E-10	3,33E-10	9,13E-11	-2,44E-08
Acidification	kg SO ₂ e	8,93E-03	6,86E-05	1,64E-03	1,06E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	5,67E-05	2,16E-04	2,76E-05	-3,56E-03
Eutrophication	kg PO ₄ ³ e	5,38E-03	1,67E-05	3,30E-03	8,70E-03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	1,40E-05	6,74E-05	7,55E-05	-6,89E-04
POCP (“smog”)	kg C ₂ H ₄ e	5,79E-04	6,12E-06	1,67E-04	7,52E-04	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	5,15E-06	1,83E-05	1,68E-05	-3,16E-04
ADP-elements	kg Sbe	2,78E-06	7,20E-08	2,13E-06	4,98E-06	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	6,39E-08	2,74E-07	1,01E-08	-5,68E-06
ADP-fossil	MJ	8,75E+01	3,77E-01	6,21E+00	9,41E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	3,16E-01	3,30E-01	9,80E-02	-2,15E+01

ADDITIONAL INDICATOR – GWP-GHG

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG ⁹⁾	kg CO ₂ e	3,42E+00	2,64E-02	4,87E-01	3,94E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,23E-02	1,36E+00	3,42E-02	-9,70E-01

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. In addition, the characterisation factors for the flows – CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide – were updated. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterisation factor for biogenic CO₂ is set to zero.

ENVIRONMENTAL IMPACTS – TRACI 2.1.

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	3,23E+00	2,60E-02	4,87E-01	3,75E+00	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	2,20E-02	1,37E+00	7,20E-02	-9,38E-01
Ozone Depletion	kg CFC-11e	3,56E-06	4,13E-10	1,43E-08	3,58E-06	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	3,81E-10	4,19E-10	1,20E-10	-3,18E-08
Acidification	kg SO ₂ e	3,84E-01	7,98E-05	1,86E-03	3,86E-01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	6,60E-05	2,72E-04	3,35E-05	-3,66E-03
Eutrophication	kg Ne	1,63E-03	8,41E-06	2,04E-03	3,68E-03	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	7,01E-06	8,23E-05	1,61E-04	-9,24E-04
POCP ("smog")	kg O ₃ e	2,23E-02	2,03E-03	3,62E-02	6,05E-02	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	1,70E-03	7,36E-03	8,33E-04	-5,87E-02
ADP-fossil	MJ	1,74E+01	3,83E-01	9,79E-02	1,79E+01	ND	ND	ND	ND	ND	ND	ND	ND	ND	0,00E+00	3,21E-01	-2,88E+01	-1,05E+01	-2,82E+01

SCENARIO DOCUMENTATION

DATA SOURCES

Manufacturing energy scenario documentation

1. Electricity, medium voltage, European attribute mix, Europe, Ecoinvent, 0.0011 kgCO₂e/kWh

End of Life scenario documentation- C1-C4 (Data source)

1. Sorting and pressing of iron scrap, Ecoinvent, Materials for recycling, 0.0079 kg
2. Treatment of scrap steel, inert material landfill, Ecoinvent, 4.2E-4 kg
3. Treatment of waste polyethylene, for recycling, unsorted, sorting, Ecoinvent, Materials for recycling, 0.23 kg
4. Treatment of waste polyethylene, for recycling, unsorted, sorting, Ecoinvent, Materials for recycling, 8.0E-4 kg
5. Treatment of waste polypropylene, municipal incineration, Ecoinvent, 0.5 kg
6. Exported Energy: Electricity, Ecoinvent, 2.59 MJ
7. Exported Energy: Thermal, Ecoinvent, 3.56 MJ
8. Treatment of waste polyethylene, sanitary landfill, Ecoinvent, 0.27 kg
9. Treatment of waste polyethylene, sanitary landfill, Ecoinvent, 4.6E-4 kg
10. Treatment of waste paperboard, unsorted, sorting, Ecoinvent, Materials for recycling, 0.38 kg
11. Treatment of waste packaging paper, municipal incineration, Ecoinvent, 0.037 kg
12. Treatment of waste packaging paper, sanitary landfill, Ecoinvent, 0.041 kg
13. Exported Energy: Electricity, Ecoinvent, 0.074 MJ
14. Exported Energy: Electricity, Ecoinvent, 0.12 MJ
15. Exported Energy: Electricity, Ecoinvent, 0.005 MJ
16. Exported Energy: Thermal, Ecoinvent, 0.11 MJ
17. Exported Energy: Thermal, Ecoinvent, 0.17 MJ
18. Exported Energy: Thermal, Ecoinvent, 0.0069 MJ
19. Treatment of waste wood, post-consumer, sorting and shredding, Ecoinvent, Materials for recycling, 0.059 kg
20. Treatment of waste wood, untreated, municipal incineration, Ecoinvent, 0.055 kg

21. Treatment of waste wood, untreated, sanitary landfill, Ecoinvent, 0.07 kg
22. Treatment of waste polyethylene, municipal incineration, Ecoinvent, 7.4E-4 kg

Scenario information	Value
Scenario assumptions e.g. transportation	To landfill: 50 km To recycling: 150 km for the product and 50 km for the packaging To incineration: 150 km for the product and 50 km for the packaging

THIRD-PARTY VERIFICATION STATEMENT

EPD Hub declares that this EPD is verified in accordance with ISO 14025 by an independent, third-party verifier. The project report on the Life Cycle Assessment and the report(s) on features of environmental relevance are filed at EPD Hub. EPD Hub PCR and ECO Platform verification checklist are used.

EPD Hub is not able to identify any unjustified deviations from the PCR and EN 15804+A2 in the Environmental Product Declaration and its project report.

EPD Hub maintains its independence as a third-party body; it was not involved in the execution of the LCA or in the development of the declaration and has no conflicts of interest regarding this verification.

The company-specific data and upstream and downstream data have been examined as regards plausibility and consistency. The publisher is responsible for ensuring the factual integrity and legal compliance of this declaration.

The software used in creation of this LCA and EPD is verified by EPD Hub to conform to the procedural and methodological requirements outlined in ISO 14025:2010, ISO 14040/14044, EN 15804+A2, and EPD Hub Core Product Category Rules and General Program Instructions.

Verified tools

Tool verifier: Magaly Gonzalez Vazquez

Tool verification validity: 27 March 2025 - 26 March 2028

Yazan Badour, as authorized verifier acting for EPD HUB Limited
30.01.2026

