Environmental Product Declaration

In accordance with ISO 14025 and EN 15804:2012+A2:2019 for:

Altech WC Pipe connector

from

Saint-Gobain Building Distribution (SGDS)



Program:	The International EPD [®] System, <u>www.environdec.com</u>
Program operator:	EPD International AB
EPD registration number:	S-P-08180
Publication date:	2023-01-26
Valid until:	2028-01-25

An EPD should provide current information and may be updated if conditions change. The stated validity is, therefore, subject to the continued registration and publication at www.environdec.com











General information

Programme information

Programme:	The International EPD [®] System								
	EPD International AB								
A daha a a .	Box 210 60								
Address:	SE-100 31 Stockholm								
	Sweden								
Website:	www.environdec.com								
E-mail:	info@environdec.com								

Product Category Rules (PCR): Construction Products PCR 2019:14 version 1.2.3

CEN standard EN 15804 serves as the Core Product Category Rules (PCR)

PCR review was conducted by: The Technical Committee of the International EPD@ System.

Life Cycle Assessment (LCA)

LCA accountability: Nadeen Hassan, EANDO AB

Third-party verification

Independent third-party verification of the declaration and data, according to ISO 14025:2006, via:

 \boxtimes EPD verification by an individual verifier

Third-party verifier: prof. Vladimír Kočí, PhD, LCA Studio, Czech Republic, vladimir.koci@lcastudio.cz

Approved by: The International EPD[®] System

The procedure for follow-up of data during EPD validity involves third-party verifier:

The EPD owner has sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but from different programmes may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804. For further information about comparability, see EN 15804 and ISO 14025.





Company information

Owner of the EPD	Saint-Gobain Distribution Sweden
Contact	SGDS - Beriar Maroof (beriar.maroof@sgdsgruppen.se)
Description of the organisation	SGDS Gruppen - specialists in collaboration for more efficient business in construction and installation. SGDS Gruppen AB is the head company of some of Sweden's leading trading companies in construction, sheet metal, tiles and installation. All the companies have long and solid industry experience and provide most of Sweden's craftsmen with materials for various projects. Customers in different companies can also buy support items from the sister companies in the group, and in selected cases, we take joint projects to facilitate the logistics of the supply of goods, which is then often critical for a smooth construction project.
	 Optimera - construction trade for professional carpenters Dahl – heat, plumbing and sanitary specialist Bevego - building sheet metal, ventilation and technical insulation Kakelspecialisten and Konradsson's Tiles - tiles, tiling and bathroom fittings
	The company focuses on sales and services with direct contact to with about 150,000 customers regularly.
	Saint-Gobain Distribution Sweden group (SGDS) is owned by Saint-Gobain with a presence in 64 countries and having over 190 000 employees worldwide.
Name and location of the production site	Bursa, Turkey
production site	MANUFACTURING








Product information

Product name	Altech WC Pipe connector
Product identification	Pipe fittings
	The EPD is a specific EPD for this product and not an average.
Product description	This product is made of EPDM, for WC connection with a hose clamp in stainless steel.
UN CPC code	34800 - Synthetic rubber and factice derived from oils - and mixtures thereof with natural rubber and similar natural gums- in primary forms or in plates, sheets or strips.
Use	Altech WC Pipe connector is used in indoor wastewater installations.

LCA information

Functional unit / declared unit	1 kg of pipe fittings
Reference service life	50 years
Database(s) and LCA software	Calculation completed in GaBi v10.6.2.9 with an integrated
used	Ecoinvent database 3.8
System boundaries	Cradle to grave, with options. (A1-A3, A4,C1-C4, D)



More information

The EPD covers the following range of products form DAHL:

Altech WC Pipe connector (with a hose clamp)





This product range is produced in the same factory and has the same material composition with a slight difference in ratios.

The worst-case product is represented in this EPD.

A1, Raw material supply

This module considers the extraction and processing of all raw materials, energy, and transportation from upstream to the studied manufacturing process.

A2, transport to the manufacturer

The raw materials are transported to the manufacturing site.

A3, manufacturing

This module includes all resources used during the production of the pipe fitting and waste produced. This also includes additives and packaging material.

A4, Transport

Transportation from the manufacturing site in Turkey to SGDS Gruppen's distribution centre and then from the distribution centre to the building site is included.

A5, Construction installation

This stage is partially included to balance the biogenic content in packaging.

B1-B7 Use stage

This stage is not declared.

C1 Deconstruction/Demolition

This stage includes the de-construction and/or demolition of the building. This is not relevant as the product included in this study is not used in the construction process.

C2 Transport

This stage represents the transport distance to the waste processing facility.

C3 Waste processing

This stage includes any waste treatment needed.

C4 Final disposal

This includes any material that is landfilled.

D Benefits and loads beyond the system boundary

Emission credits obtained from energy recovery and/or recycling materials.

Cut-off criteria:

All input and output flowsin a unit process were considered i.e., taking into account the value of all flows in the unit process and the corresponding LCI where data was available. Data gaps were filled by conservative assumptions with average or generic data. Any assumptions in such case were documented. The use of cut-off criterion on mass inputs and primary energy at the unit process level (1%) and at the information module level (5%).





Content declaration

Content

Content declaration*	Amount (kg)
EPDM	0,201
Stainless steel	0,296
Carbon black	0,211
Paraffin oil	0,177
Limestone	0,084
Sulphur	0,0104
Zinc oxide	0,0104
Stearic acid	0,0104
Total	1

*Content declaration for Altech WC Pipe connector – representing the "Worst case" scenario.

Packaging materials	Weight, kg	Weight-% (versus the product)
Polyethylene film	0,004	0,4%
Cardboard box	0,001	0,1%
Wood pallet	0,031	3,1%
Total	0,036	3,6%

No substances that appear in the REACH candidate list of SVHC (Candidate List of Substances of Very High Concern) are present or used in the product concerning this EPD.





Modules declared and geographical scope

	Proc	duct s	tage		mbly ige		Use stage						End of life stage				Benefits & loads beoyond system boundary
	Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
Modules	A1	A2	A3	A4	A5	B1	B2	B3	B4	В5	B 6	B7	C1	C2	C3	C4	D
Modules declared	х	х	х	Х	ND	ND	ND	ND	ND	ND	ND	ND	х	х	х	х	Х
Geography	TR	TR	TR	EU	-	-	-	-	-	-	-	-	EU	EU	EU	EU	EU
Specific data used	Spe	ecific data used in module A3		-	-	-	-	-	-	-	-	-	-	-	-	-	
Variation products	0,4%		-	-	-	-	-	-	-	-	-	-	-	-	-		
Variation sites		0	%		-	-	-	-	-	-	-	-	-	-	-	-	-





Environmental Information

Potential environmental impact – indicators according to EN 15804+A2

			Results per functional or declared unit: 1 kg												
Indicator	Unit	A1	A2	A3	A1-A3	Α4	A5	C1	C2	C3	C4	D			
GWP-total	kg CO2 eq	2,8E+00	3,4E-02	-1,6E-02*	2,8E+00	2,4E-01	5,4E-02	0,0E+00	6,0E-03	1,3E+00	7,1E-04	-1,7E+00			
GWP-fossil	kg CO2 eq	2,7E+00	3,2E-02	6,8E-02	2,8E+00	2,4E-01	0,0E+00	0,0E+00	6,0E-03	1,3E+00	7,2E-04	-1,7E+00			
GWP-biogenic	kg CO2 eq	8,4E-02	1,5E-03	-8,4E-02	1,1E-03	-3,3E-04	5,4E-02	0,0E+00	-8,2E-06	4,9E-05	-7,5E-06	-5,5E-03			
GWP-luluc	kg CO2 eq	1,9E-03	1,9E-06	8,3E-05	1,9E-03	1,3E-03	0,0E+00	0,0E+00	3,3E-05	4,8E-06	4,3E-07	-1,1E-03			
ODP	kg CFC-11 eq	4,8E-07	7,4E-09	3,1E-09	4,9E-07	1,4E-14	0,0E+00	0,0E+00	3,6E-16	7,6E-14	9,4E-16	-1,4E-07			
AP	mole H+ eq	1,4E-02	2,2E-04	3,3E-04	1,4E-02	4,5E-04	0,0E+00	0,0E+00	1,1E-05	1,3E-04	2,3E-06	-1,0E-02			
EP-freshwater	kg P eq	5,5E-04	3,4E-07	2,5E-05	5,7E-04	7,2E-07	0,0E+00	0,0E+00	1,8E-08	3,3E-08	5,5E-10	-1,7E-04			
EP-marine	kg N eq	2,3E-03	9,3E-05	9,2E-05	2,5E-03	1,9E-04	0,0E+00	0,0E+00	4,7E-06	3,2E-05	5,5E-07	-1,3E-03			
EP-terrestrial	mole N eq	2,5E-02	1,0E-03	9,2E-04	2,6E-02	2,1E-03	0,0E+00	0,0E+00	5,3E-05	5,8E-04	6,0E-06	-1,4E-02			
POCP	kg NMVOC eq	8,1E-03	1,9E-04	2,6E-04	8,5E-03	4,0E-04	0,0E+00	0,0E+00	1,0E-05	9,2E-05	1,7E-06	-4,9E-03			
ADP-minerals & metals	kg Sb eq	4,6E-05	5,7E-09	2,0E-07	4,6E-05	2,0E-08	0,0E+00	0,0E+00	5,0E-10	1,9E-09	5,0E-11	-4,1E-05			
ADP-fossil	MJ	6,5E+01	4,5E-01	1,1E+00	6,6E+01	3,2E+00	0,0E+00	0,0E+00	8,0E-02	2,0E-01	1,0E-02	-3,2E+01			
WDP	m3	7,2E-01	4,8E-04	1,6E-02	7,3E-01	2,2E-03	0,0E+00	0,0E+00	5,4E-05	1,1E-01	-6,8E-06	-6,4E-01			
				fuels; GWP-bioge											

Acronyms Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

*NOTE: the biogenic content in packaging contributing to the GWP-biogenic is balanced out in A5 as positive as the packaging leaves the system boundary.





Use of resources

Acronyms

			Results per functional or declared unit: 1 kg											
Indicator	Unit	A1	A2	A3	A1-A3	Α4	A5	C1	C2	СЗ	C4	D		
PERE	MJ	5,0E+00	1,2E-03	4,9E-01	5,5E+00	1,8E-01	0,0E+00	0,0E+00	4,5E-03	4,8E-02	8,3E-04	-3,2E+00		
PERM	MJ	0,0E+00	0,0E+00	6,3E-01	6,3E-01	0,0E+00								
PERT	MJ	5,0E+00	1,2E-03	1,1E+00	6,1E+00	1,8E-01	0,0E+00	0,0E+00	4,5E-03	4,8E-02	8,3E-04	-3,2E+00		
PENRE	MJ	4,4E+01	4,5E-01	1,0E+00	4,6E+01	3,2E+00	0,0E+00	0,0E+00	8,0E-02	2,0E-01	1,0E-02	-3,2E+01		
PENRM	MJ	2,1E+01	0,0E+00	4,6E-02	2,1E+01	0,0E+00								
PENRT	MJ	6,5E+01	4,5E-01	1,1E+00	6,6E+01	3,2E+00	0,0E+00	0,0E+00	8,0E-02	2,0E-01	1,0E-02	-3,2E+01		
SM	kg	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00		
RSF	MJ	0,0E+00	0,0E+00	1,0E+00	1,0E+00	0,0E+00								
NRSF	MJ	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00		
FW	m3	1,7E-02	1,1E-05	3,7E-04	1,8E-02	2,1E-04	0,0E+00	0,0E+00	5,1E-06	2,6E-03	1,4E-07	-1,7E-02		

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; P

PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy re-sources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water





Additional voluntary indicators

			Results per functional or declared unit: 1 kg											
Indicator	Unit	A1	A2	A3	A1-A3	A4	A5	C1	C2	C3	C4	D		
GWP-GHG ²	kg CO2 eq	2,6E+00	3,2E-02	6,7E-02	2,7E+00	2,4E-01	0,0E+00	0,0E+00	5,9E-03	1,3E+00	6,9E-04	-1,7E+00		
Acronyms	GWP-GHG glo	GWP-GHG global warming potential - greenhouse gases												

Waste and output flows

Waste

		Results per functional or declared unit: 1 kg										
Indicator	Unit	A1	A2	A3	A1-A3	Α4	A5	C1	C2	C3	C4	D
HWD	kg	1,6E-09	0,0E+00	1,8E-02	1,8E-02	1,5E-11	0,0E+00	0,0E+00	3,8E-13	1,8E-11	1,5E-12	-1,2E-09
NHWD	kg	9,7E-03	0,0E+00	5,0E-04	1,0E-02	4,6E-04	0,0E+00	0,0E+00	1,1E-05	3,9E-02	1,5E-02	-1,0E-01
RWD	kg	2,9E-04	0,0E+00	3,9E-08	2,9E-04	4,0E-06	0,0E+00	0,0E+00	9,8E-08	1,1E-05	1,2E-07	-4,6E-04
Acronyms	HW Hazardous waste disposed; NHW Non-hazardous waste disposed; RW Radioactive waste disposed											

² The indicator includes all greenhouse gases included in GWP-total but excludes biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. This indicator is thus almost equal to the GWP indicator originally defined in EN 15804:2012+A1:2013.





Output flows

		Results per functional or declared unit: 1 kg										
Indicator	Unit	A1	A2	A3	A1-A3	Α4	A5	C1	C2	СЗ	C4	D
CRU	kg	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00
MFR	kg	0,0E+00	0,0E+00	1,9E-02	1,9E-02	0,0E+00	0,0E+00	0,0E+00	0,0E+00	4,9E-01	0,0E+00	0,0E+00
MER	kg	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	4,9E-01	0,0E+00	0,0E+00
EEE	MJ	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00
EET	MJ	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	0,0E+00	2,0E+00	0,0E+00	0,0E+00
Acronyms	CRU Components for reuse; MR Materials for recycling; MER Materials for energy recovery; EEE Exported electric energy; ETE Exported thermal energy											

Information on biogenic carbon content

Biogenic carbon content	Unit per DU	Amount
Biogenic carbon content in product	kg C	0
Biogenic carbon content in packaging	kg C	1,46E-02

1 kg biogenic carbon is equivalent to 44/12 kg CO2.

Disclaimers

ILCD classification	Indicator	Disclaimer			
	Global warming potential (GWP)	None			
ILCD Type 1	Depletion potential of the stratospheric ozone layer (ODP)				
	Potential incidence of disease due to PM emissions (PM)				
	Acidification potential, Accumulated Exceedance (AP)	None			
	Eutrophication potential, Fraction of nutrients reaching	None			
	freshwater end compartment (EP-freshwater)	NOTE			
	Eutrophication potential, Fraction of nutrients reaching	None			
ILCD Type 2	marine end compartment (EP-marine)	None			
	Eutrophication potential, Accumulated Exceedance	None			
	(EP-terrestrial)	NONE			
	Formation potential of tropospheric ozone (POCP)	None			
	Potential Human exposure efficiency relative to U235 (IRP)	1			
	Abiotic depletion potential for non-fossil resources (ADP-minerals&metals)	2			
	Abiotic depletion potential for fossil resources (ADP-fossil)	2			
	Water (user) deprivation potential, deprivation-weighted	2			
	water consumption (WDP)	2			
ILCD Type 3	Potential Comparative Toxic Unit for ecosystems (ETP-fw)	2			
	Potential Comparative Toxic Unit for humans (HTP-c)	2			
	Potential Comparative Toxic Unit for humans (HTP-nc)	2			
	Potential Soil quality index (SQP)	2			

Disclaimer 1 – This impact category deals mainly with the eventual impact of low-dose ionizing radiation on the human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents or occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and some construction materials is also not measured by this indicator.

Disclaimer 2 – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.



References

General Programme Instructions of the International EPD® System. Version 4.	General Programme Instructions of the International EPD® System. Version 4
ISO 14020:2000 Environmental labels and declarations — General principles	ISO 14020:2000 Environmental labels and declarations — General principles
ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures	ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures
ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines	ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines
EN 15804:2012+A2:2019- Sustainability of construction works - Environmental product declaration - Core rules for the product category of construction products	EN 15804:2012+A2:2019- Sustainability of construction works - Environmental product declaration - Core rules for the product category of construction products
Construction Products PCR 2019:14 version 1.2.3	EPD International (2021): PCR 2019:14 Construction products and construction services, version 1.2.3

