

[print](#) | [close](#)

detailed view of article 3114372  
for your search 3114372

name:

customer version	DM_Germany
delivery service class	LSK 3
nominal flow	25 m <sup>3</sup> /h
nominal diameter	50 mm
body length	300 mm
connection	FL50 mm
Wechselflansch	no
connection standard	EN 1092
nominal pressure	16 bar
approval	MID
1st verification	conformity declared
dynamic range	R 800
flow unit	m <sup>3</sup> /h, 3 digits after comma
volume unit	m <sup>3</sup> , 2 digits after comma
temperature	30 °C
material	Grauguss
surface	Schwarzgrau_150
Kommunikationsmodul	-
interface module 1	Radio 868 Open Metering / L-Bus
interface module 2	Pulse
product name	HYDRUS
radio key	OMS4_Schlüssel_individuell
Funksendeschema	Fixed Network ready (T Mode)
value impulse output 1	without
value impulse output 2	forward volume 100 L/Imp.
Volumen	Total Volumen
cable length	1,5 m
Kabellänge_2	-
accounting date 1	end of June
accounting date 2	end of december
log memory interval 0	end of the month
log memory interval 1	daily
Turbator	without strainer
non return valve	without
property number	
Firmwareversion	F 1.0.8
Desinfektion	yes
meter for exchange	no
Produzierbar_DMPL	no
Versandart	standard
pps_grundtyp_baugruppe	BGA0002
pps_grundtyp	GA174007

**release status**

**active**

[print](#) | [close](#)