

[print](#) | [close](#)

detailed view of article 3112844
for your search null

name:

customer version	DM_SR2
delivery service class	LSK 3
nominal flow	40 m ³ /h
nominal diameter	65 mm
body length	300 mm
connection	FL65 mm
Wechselflansch	DN60-65
connection standard	EN 1092
nominal pressure	16 bar
approval	MID
1st verification	conformity declared
dynamic range	R 800
flow unit	m ³ /h, 3 digits after comma
volume unit	m ³ , 2 digits after comma
temperature	50 °C
material	Grauguss
surface	Schwarzgrau_150
Kommunikationsmodul	-

interface module 1	M-Bus
interface module 2	Pulse
product name	HYDRUS
radio key	-
Funksendeschema	-
value impulse output 1	forward volume 10 L/Imp.
value impulse output 2	Rückwärtsvolumen 10L/Imp.
Volumen	Total Volumen
cable length	1,5 m
Kabellänge_2	-
accounting date 1	end of december
accounting date 2	end of June
log memory interval 0	end of the month
log memory interval 1	daily
Turbator	without strainer
non return valve	without
property number	
Firmwareversion	F 1.0.8
Desinfektion	no
meter for exchange	no
Produzierbar_DMPL	no
Versandart	standard

pps_grundtyp_baugruppe	BGA0002
pps_grundtyp	GA174008

release status
date
article was unlocked by

active
17.03.2021
hegendan

[print](#) | [close](#)