

[print](#) | [close](#)

detailed view of article 3117139
for your search null

name:

customer version	DM
delivery service class	LSK 3
nominal flow	400 m³/h
nominal diameter	200 mm
body length	350 mm
connection	FL200 mm
Wechselflansch	no
connection standard	EN 1092
nominal pressure	16 bar
approval	MID
1st verification	conformity declared
dynamic range	R 800
flow unit	m³/h, 3 digits after comma
volume unit	m³, 1 digit after comma
temperature	50 °C
material	Grauguss
surface	Schwarzgrau_150
Kommunikationsmodul	-
interface module 1	Radio 868 Open Metering / L-Bus
interface module 2	Pulse
product name	HYDRUS
radio key	OMS3_Schlüssel_DMDE
Funksendeschema	Fixed Network ready (T Mode)
value impulse output 1	without
value impulse output 2	forward volume 100 L/Imp.
Volumen	Total Volumen
cable length	1,5 m
Kabellänge_2	-
accounting date 1	end of december
accounting date 2	end of June
log memory interval 0	end of the month
log memory interval 1	daily
Turbator	without strainer
non return valve	without
property number	
Firmwareversion	F 1.0.8
Desinfektion	yes
meter for exchange	no
Produzierbar_DMPL	no
Versandart	standard
pps_grundtyp_baugruppe	BGA0002
pps_grundtyp	GA174016

release status

active

[print](#) | [close](#)