

[print](#) | [close](#)

detailed view of article 3116712  
for your search 3116712

name:

customer version	DM_SE
delivery service class	LSK 3
nominal flow	16 m <sup>3</sup> /h
nominal diameter	40 mm
body length	300 mm
connection	G2B
Wechselflansch	no
connection standard	DIN ISO 228-1
nominal pressure	16 bar
approval	MID
1st verification	conformity declared
dynamic range	R 160
flow unit	m <sup>3</sup> /h, 3 digits after comma
volume unit	m <sup>3</sup> , 3 digits after comma
temperature	50 °C
material	lead-free brass
surface	unpainted
Kommunikationsmodul	-
interface module 1	Radio 868 Open Metering
interface module 2	without
product name	HYDRUS
radio key	OMS3_Schlüssel_DMDE
Funksendeschema	Fixed Network ready (T Mode)
value impulse output 1	without
value impulse output 2	without
Volumen	Total Volumen
cable length	without
Kabellänge_2	-
accounting date 1	end of december
accounting date 2	end of June
log memory interval 0	end of the month
log memory interval 1	daily
Turbator	with strainer
non return valve	without
property number	
Firmwareversion	F 1.1.1
Desinfektion	no
meter for exchange	no
Produzierbar_DMPL	no
Versandart	standard
pps_grundtyp_baugruppe	BGA0001
pps_grundtyp	GA173012

**release status**

**active**

[print](#) | [close](#)