

[print](#) | [close](#)

detailed view of article 3121873  
for your search 3121873

name:

customer version	DM_SE
delivery service class	LSK 3
nominal flow	4 m <sup>3</sup> /h
nominal diameter	20 mm
body length	130 mm
connection	G1B
Wechselflansch	no
connection standard	DIN ISO 228-1
nominal pressure	16 bar
approval	MID
1st verification	conformity declared
dynamic range	R 160
flow unit	m <sup>3</sup> /h, 3 digits after comma
volume unit	m <sup>3</sup> , 3 digits after comma
temperature	90 °C
material	lead-free brass
surface	unpainted

interface module 1	M-Bus
interface module 2	without
product name	HYDRUS
radio key	-
Funksendeschema	-
value impulse output 1	without
value impulse output 2	without
Volumen	Total Volumen
cable length	1,5 m
Kabellänge_2	-
accounting date 1	end of december
accounting date 2	end of June
log memory interval 0	end of the month
log memory interval 1	daily
strainer	with
non return valve	non-return valve
property number	
Firmwareversion	F 1.1.1
Desinfektion	no
meter for exchange	no
Produzierbar_DMPL	yes
Versandart	standard

pps_grundtyp_baugruppe	BGA0001
pps_grundtyp	GA173007

**release status**                      **active**

[print](#) | [close](#)