



A.

B.

C.

D.

E.

Cable/wiring

HeatUp Smart, kopplingsbox 24 V

24V	
2 x 2 x Ø 0.6 PDS cable (UTP or STP)	☺
H03VV-F 0.50 mm ² , flexible H03VV-F 0.75 mm ² , flexible 3 x 1.0 mm ² , solid core 3 x 1.5 mm ² , solid core	☺
5 x 1.5 mm ² > 1.5 mm ² < 24 AWG	☹

230V (3A fuse in Danfoss Icon™ Master, 24 V)	
H03VV-F 0.50 mm ² , flexible H03VV-F 0.75 mm ² , flexible	☺
3 x 1.0 or 3 x 1.5 mm ² , solid core	☺
5 x 1.5 mm ² , solid core > 1.5 mm ²	☹



A. ·)))

B. ·)))

C. ·)))

D. ·)))

E. ·)))

Cable/wiring

HeatUp Smart, kopplingsbox 24 V

230V (3A fuse in Danfoss Icon™ Master, 24 V) ⚠	
H03VV-F 0.50 mm ² , flexible	😊
H03VV-F 0.75 mm ² , flexible	😊
3 x 1.0 or 3 x 1.5 mm ² , solid core	😊
5 x 1.5 mm ² , solid core	😞
> 1.5 mm ²	😞