Heat-insulated fire hydrant cabinets with heating



Description

Basic model fire hydrant cabinets are manufactured from 1,25 mm steel and the reels are made from 1 mm galvanized steel. The cabinet has a welded back wall that strengthens the structure and a reinforced door. The doors open 180 degrees.

30 mm heat insulation. Insulated double door. Thermostat controlled 200 W electric resistor (230 V). Otherwise, the dimensions and materials are same as the basic model.

Standard

Manufactured according to EN 671-1 standard specifications.

Surface finish

Epoxy powder-coated Standard colours: -grey (RAL 7040) -white (RAL 9016) -red (RAL 3020)

Hoses

1. Fabric surface polyester/EPDM lightweight hose. Fulfils EN 694:2001 standard.

Operating pressure: 1,2 MPa Burst pressure: 9 MPa Nitrile/PVC fire hydrant hose reinforced with a polyester webbing. Fulfils EN 694:2001 Type A Class 2 standard. Operating pressure: 1,2 MPa Burst pressure: 4 MPa
The hose assembly is equipped with a spray nozzle.

Reel

The reels are painted red. The hub of the reel is made from a special pressure-tested brass casting. The reel is equipped with a spring-reinforced feed hose, a spray nozzle and a 1" shut off valve.

Lock

The door is equipped with a special lock that is shielded by a breakable protective glass (picture on the right).



Cabinet size alternatives

Surface-model		
Code	Model	Size
2954900	PV-10EL	690x690x305
2954910	PV-102EL	990x690x305
2954920	PV-202EL	690x990x305
Max hose dimensions 19 mm/25 m or 25 mm/20 m, lightweight hose 19 mm/30 m or 25 mm/25 m. Surface-model		
Code	Model	Size
2954930	PV-11EL	790x790x365
2954940	PV-112EL	1150x790x350
2954950	PV-212EL	7901150x365
Hose and nozzle are not included in price. Max hose dimensions 19 mm/45 m or 25 mm/30 m, lightweight hose 19 mm/50 m or 25 mm/35 m.		

Dimensions









