



Duo Clamp SRS ss w/Lining

Group: 1722

Application

Two-piece pipe clamp with thread connection M8 or M10 and sound absorption lining for the installation of pipelines.

Scope of delivery

Supplied with two bolts pre-screwed on one side and therefore ready for immediate installation. The clamping bolt on the open side is retained by a plastic washer, thus preventing any accidental unscrewing.

Technical Data

Type	Thread connection	Max. perm. working load (tension)	Tightening torque [Nm]
12 - 64	M8	0.6 kN	2
67 - 170	M10	2.5 kN	2

Material:

Pipe clamp:

Stainless steel A4

Sound absorption lining:

SBR/EPDM, black (see chapter "Sound Absorption Products")

Size range [mm]	For pipe [NB]	Material W x th [mm]	W [kg]	Quantity [pack]	Part number
12 - 15	1/4"	20 x 1.5	0.05	100	170693
15 - 19	3/8"	20 x 1.5	0.05	100	170709
20 - 23	1/2"	20 x 1.5	0.06	100	170718
25 - 28	3/4"	20 x 1.5	0.06	100	170727
32 - 35	1"	20 x 1.5	0.07	100	170736
40 - 45	1 1/4"	20 x 1.5	0.08	50	170745
48 - 52	1 1/2"	20 x 1.5	0.09	50	170754
52 - 58	-	20 x 1.5	0.09	50	173360
60 - 64	2"	20 x 1.5	0.10	50	170763
67 - 72	-	25 x 2.0	0.19	25	173369
73 - 80	2 1/2"	25 x 2.0	0.19	25	170772
86 - 91	3"	25 x 2.0	0.22	25	170781
102 - 108	-	25 x 2.0	0.25	25	173378
110 - 115	4"	25 x 2.5	0.29	25	170790
135 - 143	5"	25 x 2.5	0.36	25	110884
149 - 161	-	25 x 2.5	0.38	25	110885
162 - 170	6"	25 x 2.5	0.41	25	110886