



Beam Clamp TCS 1 HCP

Group: 1837

Application

Heavy-duty connection elements which, in combination with Grub Screws (M10), are suitable for mounting pipes, ducts and equipment to steel beams (I-, T-, U- and angle steel beams).

- ◆ The combination with a Universal Joint ss provides for vertically aligned attachment to inclined beams.
- ◆ Can serve as single mounting elements, for installing crossbars and for fixing cantilever structures.
- ◆ Due to their special base profile, Beam Clamps TCS 1 can also be slid along and retained in the opening of Sikla Channels MS 41.

Scope of delivery

Pre-assembled with clamping bolt and locking nut.

Installation

Tighten the clamping bolt of the Beam Clamp first by hand, then tighten down with a spanner according to the mounting instructions. The hardened point of the clamping bolt will penetrate the comparatively soft material of the beam, ensuring a solid and highly secure connection. Tighten the locking nut for securing the installation.

For use in the area of a cutting edge of a channel, an additional Holding Bracket HK 41 must be mounted.

Note: Read relevant mounting instructions before installation!

Technical Data

Working load: 5.0 kN

This nominal load applies to new Beam Clamps fixed to undamaged beam flanges only.

Material:

Approvals / Compliance

Approved and accepted by VdS and FM for use with stationary fire extinguishing systems.

For different application fields: G4820023, G4800039, G4800040, G4800044, G4800045

Type	Connection [fore/aft]	Clamping range on parallel flange [mm]	W [kg]	Quantity [pack]	Part number
TCS 1 M10	M10/M10	26	0.21	50	162151