

Underground Drainage Fittings **SN 8/SDR 34** Raccords assainissement **CR 8/SDR 34** Hulpstukken **SN 8/SDR 34**



CR 8 / SN 8 / SDR 34



Socket Plug PVC-U
Colour: grey/RAL 7037
Dimensions



Bouchon PVC-U
Couleur : gris/RAL 7037
Homologation



Afsluitkap-Spie PVC-U
Kleur: grijs/RAL 7037
Certificaat



DN/OD	Wall Thickness Epaisseur de paroi Wanddikte	Certification Certification Certificaat	Pack Quantity Pièce/Palette Stuks/pallet	Code-No.	Sealing Joint Dichting
110	3,2	1, 2, 3	1000	KGM 4 1000 K	-
125	3,2	1, 2, 3	700	KGM 4 1250 K	-
160	4,0	1, 2, 3	360	KGM 4 1500 K	-
200	4,9	1, 2, 3	220	KGM 4 2000 K	-
250	6,2	1, 2, 3	78	KGM 4 2500 K	-
315	7,7	1, 2, 3	-	COM 3000	-
400	11,7	-	-	COM 4000	-
500	14,6	-	-	COM 5000	-
630	18,4	-	-	COM 6000	-
710	20,8	-	-	COM 7000	-
800	23,4	-	-	COM 8000	-

Chamber Socket PVC-U
sandet
Dimensions

**Manchon de regard
PVC-U**
Sablé
Homologation

Putmof PVC-U
bezend
Certificaat



DN/OD	Wall Thickness Epaisseur de paroi Wanddikte	Length Longueur Lengte	Code-No.	Sealing Joint Dichting
315	9,2	150 mm ± 5 mm	COSA 300 150 B	CI
400	11,7	150 mm ± 5 mm	COSA 400 150 B	CI
500	14,6	150 mm ± 5 mm	COSA 500 150 B	CI
630	18,4	225 mm ± 5 mm	COSA 600 275 B	CI
710	20,8	255 mm ± 5 mm	COSA 700 290 B	CI
800	23,4	275 mm ± 5 mm	COSA 800 290 B	CI

Level Invert Reducer PVC-U
Colour: grey/RAL 7037
Dimensions

Augmentation PVC-U
Couleur : gris/RAL 7037
Homologation

Verloopstuk PVC-U
Kleur: grijs/RAL 7037
Certificaat



DN/OD	Wall Thickness Epaisseur de paroi Wanddikte	Certification Certification Certificaat	Pack Quantity Pièce/Palette Stuks/pallet	Code-No.	Sealing Joint Dichting
160/110	4,7/3,2	3	90	KGU 8 1510 K	FE
200/125	5,9/3,7	1, 3	90	KGU 8 2012 K	FE
200/160	5,9/4,7	1, 3	90	KGU 8 2015 K	FE
250/200	7,3/5,9	1, 3	48	KGU 8 2520 K	FE
315/250	9,2/7,3	1, 3	24	COU 3025	FE
400/315	11,7/9,2	-	-	COU 4030	CI
500/400	14,6/11,7	-	-	COU 5040	CI
630/500	18,4/14,6	-	-	COU 6050	CI
710/630	20,8/18,4	-	-	COU 7060	CI
800/710	23,4/20,7	-	-	COU 8070	CI

