

**Floorstanding WC rimless combination with cistern  
without fixing holes for floor fixation  
82896.9**



**TECHNICAL DATA**

Order no.	82896.9
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, Charge 737 with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass
Special specification	with shut-off valve, Charge 738
Outlet	horizontal VARIO, vertical 70 - 250 mm
Weight	39,5 kg
Accessories excl.	Seat and cover, order no. 89095.2, 89115.0, 89115.2 Seat and cover with automatic lowering system, order no. 89095.3, 89115.1

Mounting acc. excl.	for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 160 - 250 mm only LAUFEN-connection, order no. 89902.5
Colours	see colour table

**SPECIFICATION TEXT**

Floorstanding WC rimless washdown LAUFEN PRO N, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush)  
EN 997, 4,5/3-l-flush, dimensions 365 x 650 x 890 mm  
outlet horizontal, VARIO vertical 70 - 250 mm, back to wall  
Special feature: concealed surfaces directing water are fully glazed throughout, open water rim, vacuum checked  
Further options / accessories: Surface refinement LCC, with shut-off valve option 738, WC seat and cover 89095.2, 89115.0, 89115.2, WC seat and cover with automatic lowering 89095.3, 89115.1  
Order no. 82896.9

**TECHNICAL DRAWINGS / S 1 : 20**

