

**Floorstanding WC rimless combination
with cistern and seat and cover
without fixing holes for floor fixation**

82515.3



TECHNICAL DATA

Order no.	82515.3
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, with shut-off valve, Charge 783 with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass with seat and cover, Thermoplast, removable
Outlet	horizontal VARIO, vertical 70 - 250 mm
Weight	35,0 kg
Mounting acc. excl.	for VARIO-outlet 70 - 160 mm LAUFEN- connection, order no. 89009.2 for VARIO-outlet 160 - 250 mm only LAUFEN- connection, order no. 89902.5
Colours	see colour table

SPECIFICATION TEXT

Floorstanding WC rimless washdown Laufen-KOMPAS, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush), with seat and cover, Thermoplast, removable
EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 850 mm
outlet horizontal, VARIO vertical 70 - 250 mm, back to wall
Special feature: rimless, concealed surfaces directing water are fully glazed throughout, vacuum checked
Further options: Surface refinement LCC
Order no. 82515.3

TECHNICAL DRAWINGS / S 1 : 20

