

# Floorstanding WC combination with cistern and seat and cover with fixing holes for floor fixation

## 82536.2



### TECHNICAL DATA

Order no.	82536.2
Certified to	EN 997
Specification	Washdown for 4,5/3-l-flush, with shut-off valve, Charge 783 4 fixing holes with cistern flushing mechanism, water condensation insulation, Dual-Flush (4,5/3-l-flush), water inlet bottom right 1/2" brass with seat and cover, Thermoplast, removable
Outlet	horizontal VARIO, vertical 70 - 200 mm
Weight	32,0 kg
Accessories incl.	2x fastening kit, order no. 89128.2 Seat and cover, Thermoplast, order no. 89037.1 Shut-off valve, order no. 89283.0

Mounting acc. excl.	for VARIO-outlet 70 - 160 mm LAUFEN-connection, order no. 89009.2 for VARIO-outlet 160 - 200 mm only LAUFEN-connection, order no. 89902.5
---------------------	--

Colours see colour table

### SPECIFICATION TEXT

Floorstanding WC pan washdown Laufen-RIGO, sanitary ceramic, with cistern Dual-Flush (4,5/3-l-flush), with seat and cover, Thermoplast, removable EN 997, 4,5/3-l-flush, dimensions 360 x 650 x 850 mm outlet horizontal, VARIO vertical 70 - 200 mm back to wall, 4 fixing holes  
Special feature: concealed surfaces directing water are fully glazed throughout, vacuum checked  
Order no. 82536.2

### TECHNICAL DRAWINGS / S 1 : 20

