



Den enda sömlösa rörböjen på marknaden som är 100% tryckklassenlig.

EN-class conform-böjar:
Håller alltid samma kvalitet och tjocklek som röret, oavsett var på böjen man mäter.
Gäller alla gradantal.

ESB 30°

Sömlösa böjar. EN 1555 & EN 12201. $r \approx 1,5 \times d$

SDR11 PN16

1,0

PE100 RC+

EN12201

EN1555



Lev nr	RSK-nr	d (d1)	le1*	z1	r	Vikt (kg)	Status
ESB 30° 50	2432063	50	100	150	75	0,20	✓
ESB 30° 63	2432069	63	100	160	95	0,30	✓
ESB 30° 75	2432075	75	100	170	113	0,50	✓
ESB 30° 90	2432081	90	150	210	135	0,80	✓
ESB 30° 110	2431147	110	150	220	165	1,30	✓
ESB 30° 125	2431148	125	150	235	188	1,80	✓
ESB 30° 140	2431149	140	150	250	210	2,40	✓
ESB 30° 160	2431150	160	150	260	240	3,30	✓
ESB 30° 180	2431151	180	150	280	270	4,50	✓
ESB 30° 200	2431152	200	150	310	300	6,10	✓
ESB 30° 225	2431153	225	150	350	338	8,80	✓
ESB 30° 250	2431154	250	250	430	375	13,30	✓
ESB 30° 280	2431155	280	250	450	420	17,40	✓
ESB 30° 315	2431156	315	300	500	496	24,50	✓
ESB 30° 355	2431157	355	300	590	560	36,80	✓
ESB 30° 400	2431158	400	300	650	637	51,40	✓
ESB 30° 450	2431159	450	300	700	711	70,20	✓
ESB 30° 500	2431160	500	350	750	783	92,70	✓
ESB 30° 560	2431161	560	350	800	877	123,90	✗
ESB 30° 630	2431162	630	350	850	955	166,80	✗
ESB 30° 710	2431604	710	350	1150	1128	287,00	✗
ESB 30° 800	2540062	800	350	1250	1274	395,60	✗
ESB 30° 900	2540063	900	400	1350	1430	540,70	✗

Sömlösa böjar kan ha en tolerans på +/-3°. Alla mått i mm. * = minsta längd
Går att beställa i valfritt gradantal, större radie samt i andra material.