



Den enda sömlösa rörböjen på marknaden som är 100% tryckklassenlig.

EN-class conform-böjar:
Håller alltid samma kvalitet och tjocklek som röret, oavsett var på böjen man mäter.
Gäller alla gradantal.

ESB 60°

Sömlösa böjar. EN 1555 & EN 12201. $r \approx 1,5 \times d$

SDR11 PN16

1,0

PE100 RC+

EN12201

EN1555



Lev nr	RSK-nr	d (d1)	le1*	z1	r	Vikt (kg)	Status
ESB 60° 50	2432065	50	100	170	75	0,20	x
ESB 60° 63	2432071	63	100	180	95	0,30	x
ESB 60° 75	2432077	75	100	220	113	0,60	x
ESB 60° 90	2432083	90	150	250	135	1,00	x
ESB 60° 110	2431179	110	150	280	165	1,60	x
ESB 60° 125	2431180	125	150	300	188	2,30	x
ESB 60° 140	2431181	140	150	350	210	3,30	x
ESB 60° 160	2431182	160	150	380	240	4,70	x
ESB 60° 180	2431183	180	150	410	270	6,40	x
ESB 60° 200	2431184	200	150	430	300	8,30	x
ESB 60° 225	2431185	225	150	450	338	10,90	x
ESB 60° 250	2431186	250	250	570	375	17,10	x
ESB 60° 280	2431187	280	250	580	420	21,70	x
ESB 60° 315	2431188	315	300	690	496	32,80	x
ESB 60° 355	2431189	355	300	760	560	45,70	x
ESB 60° 400	2431190	400	300	780	637	59,40	x
ESB 60° 450	2431191	450	300	820	711	78,90	x
ESB 60° 500	2431192	500	350	960	783	114,20	x
ESB 60° 560	2431193	560	350	980	877	145,50	x
ESB 60° 630	2431194	630	350	1200	955	226,90	x
ESB 60° 710	2540066	710	350	1450	1128	348,80	x
ESB 60° 800	2540067	800	350	1500	1274	455,90	x
ESB 60° 900	2540068	900	400	1650	1430	634,20	x

Sömlösa böjar kan ha en tolerans på +/-3°. Alla mått i mm. * = minsta längd
Går att beställa i valfritt gradantal, större radie samt i andra material.