

# WASTOP® INLINE CHECK VALVE

## WaStop 290

<b>Model Name</b>	WS290
<b>Nominal Diameter</b>	DN 300
<b>Fasteners mtrl.</b>	EN 1.4404
<b>Gasket Mtrl.</b>	EPDM
<b>Weight [kg]</b>	10
<b>Min. ID Host Pipe [mm]</b>	292
<b>Max. ID Host Pipe [mm]</b>	308
<b>Max. Flow Vel. [m/s]</b>	3
<b>Max. Flow Vol. [l/s]</b>	198

## Product Variants

<b>Art. No</b>	<b>WS290-S3-316</b>
<b>Membrane mtrl.</b>	EPDM
<b>Valve Body mtrl.</b>	EN 1.4404
<b>Max. Back Pressure [mH<sub>2</sub>O]</b>	5
<b>Horizontal Opening [mmH<sub>2</sub>O]</b>	220
<b>Horizontal Closing [mmH<sub>2</sub>O]</b>	135
<b>Submerged Opening [mmH<sub>2</sub>O]</b>	145
<b>Submerged Closing [mmH<sub>2</sub>O]</b>	45
<b>Vertical Opening [mmH<sub>2</sub>O]</b>	335
<b>Vertical Closing [mmH<sub>2</sub>O]</b>	195

