

DuraSystem® Pre-installation kit, hygienic flush for mains operation # WD6004000000



Pre-installation kit, hygienic flush for mains operation	Dimension	Weight	Order number
for panel thickness 7 - 35 mm, Scope of delivery, power supply 100-240 V AC 50/60 Hz with connection cable, concealed outlet for drilling hole \varnothing 68 mm , cover for concealed outlet, conduit pipe, length 1.7 m, for power supply of the hygienic flush, mains operation			
Colors			
999 #general.colorname_999			
Variant			
		0.400 kilogram	WD6004000000
Installation accessories			
Toilet frame, Basic self-supporting, for drywall construction, suitable for panelling with plasterboards, powder-coated frame, for WC ceramics with a projection of \leq 625 mm, adjustable feet 0-240 mm, mechanical front actuation, flattenings for optimal access of press tools, metre tear and center marker, tool-free assembly of the transparent service opening plate, Requirements of the leading standards of noise protection DIN 4109 and VDI 4100 can be achieved (in combination with noise reduction set # WD6015 000 000), Cistern, concealed cistern CE tested in accordance with EN 14055, maximum flush volume 9l, marking of filling height, Dual flush technology, adjustable flush volume, insulated against condensation, throttle for adjustment of the flushing flow, Scope of delivery, PE-wall-mounted toilet connection bend DN 90/90, PE-wall-mounted toilet connection set DN 90, wall-mounted toilet fastening set M12, PE-wall-mounted toilet reduction DN 90/110 for outlet bend, 2 cover caps, pre-installed toilet frame for wall-mounted toilet	500 x 1148 mm	14.400 kilogram	WD1020

DuraSystem® Pre-installation kit, hygienic flush for mains operation # WD6004000000

<p>Toilet frame, standard self-supporting, for drywall construction, suitable for panelling with plasterboards, powder-coated frame, for WC ceramics with a projection of <= 625 mm, adjustable feet 0–240 mm, SensoWash ready, mechanical front actuation, flattenings for optimal access of press tools, metre tear and center marker, tool-free assembly of the transparent service opening plate, Requirements of the leading standards of noise protection DIN 4109 and VDI 4100 can be achieved (in combination with noise reduction set # WD6015 000 000), Cistern, concealed cistern CE tested in accordance with EN 14055, maximum flush volume 9l, marking of filling height, Dual flush technology, adjustable flush volume, insulated against condensation, throttle for adjustment of the flushing flow, Scope of delivery, PE-wall-mounted toilet connection bend DN 90/90, PE-wall-mounted toilet connection set DN 90, wall-mounted toilet fastening set M12, mounting accessoires for lightweight construction, mounting accessoires for single installation, PE-wall-mounted toilet reduction DN 90/110 for outlet bend, 2 cover caps, pre-installed toilet frame for wall-mounted toilet</p>	500 x 1148 mm	WD1011	
<p>Toilet frame, for wet installation flattenings for optimal access of press tools, tool-free assembly of the transparent service opening plate, to wall-in or bricking up, galvanized slit strip, mechanical front actuation, Cistern, concealed cistern CE tested in accordance with EN 14055, maximum flush volume 9l, marking of filling height, Dual flush technology, adjustable flush volume, insulated against condensation, throttle for adjustment of the flushing flow, Scope of delivery, PE-wall-mounted toilet connection bend DN 90/90, PE-wall-mounted toilet connection set DN 90, wall-mounted toilet fastening set M12, PE-wall-mounted toilet reduction DN 90/110 for outlet bend, 2 cover caps, pre-installed toilet frame for wall-mounted toilet</p>	445 x 915 mm	6.700 kilogram	WD1015

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.