

**DuraSystem® Flush-mounted installation frame, for plastic #**  
**WD6001..1000 / WD6001..1000**

| < 224,4 mm > |



Flush-mounted installation frame, for plastic	Dimension	Weight	Order number
for flush mounted installation, adjustable in depth, for wall coverings 6 - 15 mm , for drywall construction plating with minimum thickness 2 x 12,5 mm, plastic			
<b>Colors</b>			
00 White Alpin 10 Chrome			
<b>Variant</b>			
white	224,4 x 154 mm	0.300 kilogram	WD6001..1000
	224,4 x 154 mm	0.300 kilogram	WD6001..1000
<b>Infobox</b>			
The flush mounted installation frame is needed for the panelling during the installation process. Suitable for drywall construction plating with a minimum thickness of 25 mm. , The actuator plate A1 in plastic could be flush-mounted (except wet installation and elements with reduced height). For the flush-mounted installation the installation frame #WD6001 011 000 (white) or #WD6001 021 000 (chrome highgloss) must be ordered.			
<b>Installation accessories</b>			
Toilet frame, Basic self-supporting, for drywall construction, suitable for panelling with plasterboards, powder-coated frame, for WC ceramics with a projection of <= 625 mm, adjustable feet 0-240 mm, mechanical front actuation, flattenings for optimal access of press tools, metre tear and center marker, tool-free assembly of the transparent service opening plate, Requirements of the leading standards of noise protection DIN 4109 and VDI 4100 can be achieved (in combination with noise reduction set # WD6015 000 000), Cistern, concealed cistern CE tested in accordance with EN 14055, maximum flush volume 9l, marking of filling height, Dual flush technology, adjustable flush volume, insulated against condensation, throttle for adjustment of the flushing flow, Scope of delivery, PE-wall-mounted toilet connection bend DN 90/90, PE-wall-mounted toilet connection set DN 90, wall-mounted toilet fastening set M12, PE-wall-mounted toilet reduction DN 90/110 for outlet bend, 2 cover caps, pre-installed toilet frame for wall-mounted toilet	500 x 1148 mm	14.400 kilogram	WD1020

**DuraSystem® Flush-mounted installation frame, for plastic #**  
**WD6001..1000 / WD6001..1000**

| < 224,4 mm > |

<p>Toilet frame, manual odor extraction self-supporting, for drywall construction, suitable for panelling with plasterboards, powder-coated frame, for WC ceramics with a projection of &lt;= 625 mm, adjustable feet 0–240 mm, SensoWash ready, mechanical front actuation, metre tear and center marker, tool-free assembly of the transparent service opening plate, Requirements of the leading standards of noise protection DIN 4109 and VDI 4100 can be achieved (in combination with noise reduction set # WD6015 000 000), odor extraction with integrated fan, fan operation manual, airtight check valve, Cistern, concealed cistern CE tested in accordance with EN 14055, maximum flush volume 9l, marking of filling height, Dual flush technology, adjustable flush volume, insulated against condensation, throttle for adjustment of the flushing flow, Scope of delivery, pre-installation kit including power supply 100-240 V AC / 24 V DC, PE-wall-mounted toilet connection bend DN 90/90, PE-wall-mounted toilet connection set DN 90, wall-mounted toilet fastening set M12, mounting accessoires for lightweight construction, mounting accessoires for single installation, PE-wall-mounted toilet reduction DN 90/110 for outlet bend, 2 cover caps, pre-installed toilet frame for wall-mounted toilet</p>	<p>500 x 1148 mm</p>	<p>WD1012</p>	
<p>Toilet frame, standard self-supporting, for drywall construction, suitable for panelling with plasterboards, powder-coated frame, for WC ceramics with a projection of &lt;= 625 mm, adjustable feet 0–240 mm, SensoWash ready, mechanical front actuation, flattenings for optimal access of press tools, metre tear and center marker, tool-free assembly of the transparent service opening plate, Requirements of the leading standards of noise protection DIN 4109 and VDI 4100 can be achieved (in combination with noise reduction set # WD6015 000 000), Cistern, concealed cistern CE tested in accordance with EN 14055, maximum flush volume 9l, marking of filling height, Dual flush technology, adjustable flush volume, insulated against condensation, throttle for adjustment of the flushing flow, Scope of delivery, PE-wall-mounted toilet connection bend DN 90/90, PE-wall-mounted toilet connection set DN 90, wall-mounted toilet fastening set M12, mounting accessoires for lightweight construction, mounting accessoires for single installation, PE-wall-mounted toilet reduction DN 90/110 for outlet bend, 2 cover caps, pre-installed toilet frame for wall-mounted toilet</p>	<p>500 x 1148 mm</p>	<p>WD1011</p>	
<p>Actuator plate A1, for toilet, plastic mechanical actuation, for surface mounted installation, Dual flush technology, Scope of delivery, installation frame, mounting accessoires, push rods, front plate plastic</p>	<p>217 x 146,5 mm</p>	<p>0.300 kilogram</p>	<p>WD5001</p>

*All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in mm and are non-binding. Exact measurements, in particular for customised installation scenarios, can only be taken from the finished piece.*