


# PRIMOFIT®



## Koppling invändig gänga, galvaniserad för PE SDR 11/S 5 till Rp/ISO 7

\*\*\*enligt EN 1555-2




	Dim. PE [mm]	Dim. Rp [inch]	NBR Beställningsnr.	RSK	SP	kg	D [mm]	L [mm]	x [mm]
***	20 x 2,0	1/2	775 212 201	154 09 28	30	0,227	45	58	31 - 33
	25 x 2,3	3/4	775 212 202	154 09 29	20	0,300	51	62	31 - 33
	25 x 3,0	3/4	775 212 442	154 09 30	0	0,300	51	62	31 - 33
	32 x 3,0	1	775 212 203	154 09 31	1	0,400	59	68	31 - 33
	40 x 3,7	1 1/4	775 212 204	154 09 32	5	0,560	68	70	32 - 38
	50 x 4,6	1 1/2	775 212 205	154 09 33	5	0,700	75	75	35 - 43
	63 x 5,8	2	775 212 206	154 09 34	5	1,308	96	83	39 - 47



## Vinkel, galvaniserad för ISO 65 stålrör till PE SDR 11/S 5

\*\*\*enligt EN 1555-2



	Dim. Stål [inch]	Dim. PE [mm]	NBR Beställningsnr.	RSK	SP	kg
***	3/4	25 x 2,3	775 402 502	154 09 49	10	0,460
	3/4	25 x 3,0	775 402 442	154 09 50	0	0,460
	1	32 x 3,0	775 402 503	154 09 51	10	0,660
	1 1/4	40 x 3,7	775 402 504	154 09 52	5	0,889
	1 1/2	50 x 4,6	775 402 505	154 09 53	5	1,140
	2	63 x 5,8	775 402 506	154 09 54	0	1,615

	Dim. Stål [inch]	Dim. PE [mm]	D [mm]	L [mm]	x [mm]	x1 [mm]
***	3/4	25 x 2,3	51	59	30 - 34	31 - 33
	3/4	25 x 3,0	51	59	30 - 34	31 - 33
	1	32 x 3,0	59	59	30 - 34	31 - 33
	1 1/4	40 x 3,7	68	59	30 - 36	32 - 38
	1 1/2	50 x 4,6	75	78	32 - 38	35 - 43
	2	63 x 5,8	96	75	36 - 42	39 - 47