


PRIMOFIT®


PE X PE, galvaniserad

Koppling, kort, galvaniserad Rak koppling för PE SDR 11/S 5



Dim. PE [mm]	NBR Beställningsnr.	RSK	SP	kg	D [mm]	L [mm]	x [mm]	
20 x 2,0	775 102 201	154 13 60	20	0,358	45	82	31 - 33	
25 x 2,3	775 102 202	154 13 61	10	0,468	51	86	31 - 33	
32 x 3,0	775 102 203	154 13 62	10	0,549	59	93	31 - 33	
40 x 3,7	775 102 204	154 13 63	10	0,697	68	94	32 - 38	
50 x 4,6	775 102 205	154 13 64	5	1,068	75	103	35 - 43	
63 x 5,8	775 102 206	154 13 65	5	1,920	96	111	39 - 47	


Vinkel, galvaniserad för PE SDR 11/S5



Dim. PE [mm]	NBR Beställningsnr.	RSK	SP	kg	D [mm]	L [mm]	x [mm]	
20 x 2,0	775 402 201			0,339	45	58	31 - 33	
25 x 2,3	775 402 202	154 13 77		0,508	51	59	31 - 33	
32 x 3,0	775 402 203			0,664	59	59	31 - 33	
40 x 3,7	775 402 204			0,729	68	59	32 - 38	
50 x 4,6	775 402 205			1,068	75	78	35 - 43	
63 x 5,8	775 402 206	154 13 78		2,236	96	75	39 - 47	

Huv, galvaniserad för PE SDR 11/S 5

***enligt EN 1555-2



Dim. PE [mm]	NBR Beställningsnr.	RSK	SP	kg	D [mm]	L [mm]	x [mm]	
20 x 2,0	775 452 201	154 13 85	30	0,200	45	46	31 - 33	
25 x 2,3	775 452 202	154 13 86	30	0,240	51	48	31 - 33	
25 x 3,0	775 452 442	154 13 87	0	0,240	51	48	31 - 33	
32 x 3,0	775 452 203	154 13 88	15	0,329	59	52	31 - 33	
40 x 3,7	775 452 204	154 13 89	10	0,492	68	53	32 - 38	
50 x 4,6	775 452 205	154 13 90	10	0,620	75	57	35 - 43	
63 x 5,8	775 452 206	154 13 91	5	1,140	96	60	39 - 47	